


FIXED


GUA-SFWH-F-...-SP...				
Delivered Lumens - Spot				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	540	939	2810
	30	540	978	2928
	40	584	1034	3090
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		0.18	0.33	1.00



Beam Angle (0-180) = 18.4
Beam Angle (90-270) = 18.2

CONE OF LIGHT - 33.6W 3000K Spot GUA-SFWH-F-91-34-IND-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	4775	0.6
4	1194	1.3
6	531	1.9
8	298	2.6
10	191	3.2
12	133	3.9
14	97	4.5
16	75	5.2
18	59	5.8
20	49	6.5


GUA-SFWH-F-...-FL...				
Delivered Lumens - Flood				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	569	1099	3160
	30	569	1145	3294
	40	614	1209	3476
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		0.17	-	1.00



Beam Angle (0-180) = 32.0
Beam Angle (90-270) = 31.4

CONE OF LIGHT - 33.6W 3000K Flood GUA-SFWH-F-91-34-IND-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	2856	1.1
4	714	2.3
6	317	3.4
8	179	4.6
10	114	5.7
12	79	6.9
14	58	8.0
16	45	9.2
18	35	10.3
20	29	11.5

GUA-SFWH-F-...-WFL...				
Delivered Lumens - Wide Flood				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	504	1063	2726
	30	504	1089	2840
	40	544	1149	2999
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		0.18	0.38	1.00




Beam Angle (0-180) = 57.4
Beam Angle (90-270) = 57.2

CONE OF LIGHT - 33.6W 3000K Wide Flood GUA-SFWH-F-91-34-IND-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	894	2.2
4	224	4.4
6	99	6.6
8	56	8.8
10	36	10.9
12	25	13.1
14	18	15.3
16	14	17.5
18	11	19.7
20	9	21.9

* Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

FIXED HONEYCOMB


GUA-SFWH-FHC-...-SP..			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		61 [13 CC]	91 [34 IND]
CCT	27	625	1529
	30	651	1593
	40	687	1681
		Polar Plot / Cone Of Light Multiplier	
		61 [13 CC]	91 [34 IND]
		0.41	1.00



Beam Angle (0-180) = 17.8
Beam Angle (90-270) = 18.0

CONE OF LIGHT - 33.6W 3000K Spot		
GUA-SFWH-FHC-91-34-IND-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	2971	0.6
4	743	1.3
6	330	1.9
8	186	2.5
10	119	3.1
12	83	3.8
14	61	4.4
16	46	5.0
18	37	5.6
20	30	6.3


GUA-SFWH-FHC-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		61 [13 CC]	91 [34 IND]
CCT	27	669	1744
	30	697	1817
	40	736	1919
		Polar Plot / Cone Of Light Multiplier	
		61 [13 CC]	91 [34 IND]
		0.38	-



Beam Angle (0-180) = 28.0
Beam Angle (90-270) = 27.6

CONE OF LIGHT - 33.6W 3000K Flood		
GUA-SFWH-FHC-91-34-IND-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft*]
2	1916	1.0
4	479	2.0
6	213	3.0
8	120	4.0
10	77	5.0
12	53	6.0
14	39	7.0
16	30	8.0
18	24	9.0
20	19	10.0

GUA-SFWH-FHC-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		61 [13 CC]	91 [34 IND]
CCT	27	473	1133
	30	493	1182
	40	522	1247
		Polar Plot / Cone Of Light Multiplier	
		61 [13 CC]	91 [34 IND]
		0.42	1.00




Beam Angle (0-180) = 42.0
Beam Angle (90-270) = 40.0

CONE OF LIGHT - 33.6W 3000K Wide Flood		
GUA-SFWH-FHC-91-34-IND-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	592	1.5
4	148	3.1
6	66	4.6
8	37	6.1
10	24	7.7
12	16	9.2
14	12	10.7
16	9	12.3
18	7	13.8
20	6	15.4

* Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

ADJUSTABLE


GUA-SFWH-A-...-SP... Delivered Lumens - Spot				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	625	876	2996
	30	625	914	3123
	40	675	965	3295
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		0.20	0.29	1.00



Beam Angle (0-180) = 18.2
Beam Angle (90-270) = 18.0

CONE OF LIGHT - 33.6W 3000K Spot GUA-SFWH-A-91-34-IND-30-SP'		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	5144	0.6
4	1286	1.3
6	572	1.9
8	321	2.6
10	206	3.2
12	143	3.8
14	105	4.5
16	80	5.1
18	64	5.8
20	51	6.4


GUA-SFWH-A-...-FL... Delivered Lumens - Flood				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	559	979	2946
	30	559	1021	3069
	40	604	1078	3241
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		0.18	-	1.00



Beam Angle (0-180) = 34.2
Beam Angle (90-270) = 34.0

CONE OF LIGHT - 33.6W 3000K Flood GUA-SFWH-A-91-34-IND-30-FL'		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	1949	1.2
4	487	2.5
6	217	3.7
8	122	4.9
10	78	6.2
12	54	7.4
14	40	8.6
16	30	9.8
18	24	11.1
20	19	12.3


GUA-SFWH-A-...-MWFL... Delivered Lumens - Medium Wide Flood				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	-	1136	2858
	30	-	1183	2979
	40	-	1249	3144
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		-	0.40	1.00



Beam Angle (0-180) = 58.0
Beam Angle (90-270) = 59.2

CONE OF LIGHT - 33.6W 3000K Medium Wide Flood GUA-SFWH-A-91-34-IND-30-MWFL'		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	801	2.2
4	200	4.4
6	89	6.7
8	50	8.9
10	32	11.1
12	22	13.3
14	16	15.5
16	13	17.7
18	10	20.0
20	8	22.2

GUA-SFWH-A-...-WFL... Delivered Lumens - Wide Flood				
		Diameter [Wattage]		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
CCT	27	573	-	-
	30	573	-	-
	40	619	-	-
		Polar Plot / Cone Of Light Multiplier		
		43 [7 CC]	61 [13 CC]	91 [34 IND]
		1.00	-	-



Beam Angle (0-180) = 60.0
Beam Angle (90-270) = 60.4

CONE OF LIGHT - 7.2W 3000K Wide Flood GUA-SFWH-A-43-7-CC-30-WFL'		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	137	2.3
4	34	4.6
6	15	6.9
8	9	9.2
10	5	11.5
12	4	13.9
14	3	16.2
16	2	18.5
18	2	20.8
20	1	23.1

* Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.