inter•lux



General: Paseo is a complete range of compact linear LED fixtures suitable to illuminate outdoor architectural elements or used as pathway lighting thanks to its Opaline version. Its 0.9" width makes Paseo one of the slimmest and most attractive products on the market. Paseo's versatility is given by multiple mounting accessories that allow to install the same fixture recessed in ground, wall, ceiling or surface mounted applications.

Fixture Body: Clear, UV resistant Polycarbonate.

Mounting/Housing: Multiple mounting Housings available. Anodized Aluminum recessed Housings for in-ground, wall or ceiling mount, with or without frame. Adjustable brackets for cove installation. Refer to accessory page for specific options.

Drive-over: Walk-Over only.

Dimensions/Weight: 22.7" (0.86 lbs) – 45.4" (1.96 lbs)

Driver: Integral, 120V with DMX on board.

Wattages: 9W (22.7") – 19W (45.4")

Cable: Fixture comes with 0.82' of cable (Power cable required, ordered separately). **Safety features:** Built-in Aquastop[®] (Anti-wicking) and TCS[®] (Over tension and electrical

discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins. **IK rating:** IK 08 **ETL Certification:** ETL, wet location

Optics: Fixed, with Elliptic distribution.

Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White. **CRI:** 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°. **Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



22.7" (9W) 45.4" (19W)

Nominal Lumens*	22.7"	45.4"
Red	156	312
Green	272	544
Blue	92	189
White 3K	404	808
White 4K	430	860
*Values shown for 3000K		

Ordering Information								
PA	Х	С				EL		
Product	Power	Туре	Length	Wattage/Operation	Color Temp	Optic	+	Cables (Required) ¹
PA = Paseo	X = Extra Power	C = Clear	23 = 22.7"	9 IDMX = 9W / Integral 120VAC + DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	EL = Elliptic/Grazer		E83043 E83044 E83045 E83046 E83047 E89365
			45 = 45.4"	19 IDMX = 19W / Integral 120VAC + DMX interface				E89186 E98493 E98994 E98993 E89187 E89564

¹See page 2




Housings & fixing systems Order separately, see pages 3-6






inter-lux

22.7" 9W IDMX



45.4" 19W IDMX



Cables (*one power feed cable, one DMX feed cable and one DMX terminator required)

E83043*	E83044*	E83045	E83046	E83047	E89365*
59" line volt. power feed cable F 3 pin M12	196" line volt. power feed cable F 3 pin M12	39" line volt. power extension cable for M+F 4 pin M12	196" line volt. power extension cable for M+F 4 pin M12	393" line volt. power extension cable for M+F 4 pin M12	DMX Terminator
E89186*	E98493*	E98994	E98993	E89187	E89564
196" DMX cable M 5 pin M12+ M 3 pin XLR	196" DMX cable M 5 pin M12+ M 5 pin XLR	39" DMX extension 0-10V M+F 5 pin M12	196" DMX extension 0-10V M+F 5 pin M12	393" DMX extension 0-10V M+F 5 pin M12	DMX addresser






inter•lux

Paseo | Floor with trim outer housing





		Outer housing	Cable gland
Anod. Al.	20.2 in x Paseo 20.2 in	E98355	E98471
Anod. Al.	22.7 in x Paseo 22.7 in	E98430	E98472
Anod. Al.	45.4 in x Paseo 45.4 in	E98356	E98473
Anod. Al.	57.2 in x Paseo 57.2 in	E98357	E98474



Installation accessories



Paseo | Floor trimless / Surface mount outer housing






1.9

0.9

	Outer housing	Cable gland
Anod. Al. 20.2 in x Paseo 20.2 in	E98467	E98471
Anod. Al. 22.7 in x Paseo 22.7 in	E98468	E98472
Anod. Al. 45.4 in x Paseo 45.4 in	E98469	E98473
Anod. Al. 57.2 in x Paseo 57.2 in	E98470	E98474



Installation accessories








inter•lux

Paseo | Ceiling with trim outer housing





Anod. Al.	20.2 in x Paseo 20.2 in	E98374
Anod. Al.	22.7 in x Paseo 22.7 in	E98435
Anod. Al.	45.4 in x Paseo 45.4 in	E98375
Anod. Al.	57.2 in x Paseo 57.2 in	E98376



1


ŀ

Installation accessories



Paseo | Ceiling trimless outer housing





Anod. AL. 20.2 in x Paseo 20.2 in	E98367
Anod. Al. 22.7 in x Paseo 22.7 in	E98434
Anod. Al. 45.4 in x Paseo 45.4 in	E98368
Anod. Al. 57.2 in x Paseo 57.2 in	E98369



Installation accessories









inter•lux

Paseo | Surface 3D outer housing





Anod. Al.	20.2 in x Paseo 20.2 in	E98836
Anod. Al.	22.7 in x Paseo 22.7 in	E98839
Anod. Al.	45.4 in x Paseo 45.4 in	E98837
Anod. Al.	57.2 in x Paseo 57.2 in	E98838



Installation accessories




Paseo | Surface adjustable outer housing



1.2	
	-LÒD 1.2

Anod. Al. 20.4 in x Paseo 20.2 in	E98842
Anod. Al. 22.9 in x Paseo 22.7 in	E98843
Anod. Al. 45.6 in x Paseo 45.4 in	E98844
Anod. Al. 57.4 in x Paseo 57.2 in	E98845



Installation accessories








inter•lux


Paseo | Adjustable mounting clips





Mounting plate for uneven horizontal surfaces

(ordered separately)



0.1

E98771

Pair of fastening clips made of transparent polycarbonate to install the fixture in an even horizontal mounting surface. A directional accessory that allows Paseo tilt movement from + 90° to -90°.


L inches		L1 inches		
11.8 in 7.9 in		E98772		
Plate for 20	.2 or 20.7" Pa	seo fixtures		
L inche	S	L1 inches		
37.4 in 33.5 in		E98773		
Plate for45.4 or 57.2" Paseo fixtures				

The plate, without fixing it to the surface, can be used as a mobile support for the adjustable clips and fixture. Clips not included in codes E98772 - E98773 (ordered separately)

Paseo | Extraction key







E98475

The Paseo extraction key (ordered separately) allows its removal from the outer housing. Compatible with all Paseo outer housings.



