inter•lux



General: Paseo is a complete range of compact linear LED fixtures suitable to illuminate outdoor architectural elements or used as pathway lighting thanks to its Opaline version. Its 0.9" width makes Paseo one of the slimmest and most attractive products on the market. Paseo's versatility is given by multiple mounting accessories that allow to install the same fixture recessed in ground, wall, ceiling or surface mounted applications.

Fixture Body: Opaline, UV resistant Polycarbonate.

Mounting/Housing: Multiple mounting Housings available. Anodized Aluminum recessed Housings for in-ground, wall or ceiling mount, with or without frame. Adjustable brackets for cove installation. Refer to accessory page for specific options.

Drive-over: Walk-Over only.

Dimensions/Weight: 20.2" (0.86 lbs) – 45.4" (1.96 lbs) – 57.2" (3.06 lbs)

Driver: Remote 120/277VAC-24VDC driver + with DMX interface on board.

Wattages: 6W (20.2") - 13W (45.4") - 19W (57.2")

Cable: Fixture comes with 0.82' of cable (Power cable required, ordered separately). **Safety features:** Built-in Aquastop[®] (Anti-wicking) and TCS[®] (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins. IK rating: IK 08 ETL Certification: ETL, wet location

Optics: Fixed, with General/Diffused distribution.

Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White. **CRI:** 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°. **Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



20.2"(6W) 45.4"(13W) 57.2"(19W)

Nominal Lumens	20.2"	45.4"
Red	108	288
Green	144	384
Blue	72	192
White 3K/4K	252 / 272	672 / 725

Ordering In	Ordering Information (Required)						red)		
PA	L	0				GE			
Product	Power	Туре	Length	Wattage/Operation	Color Temp	Optic	+	Driver ¹	
PA = Paseo	L = Low Power	O = Opaline	20 = 20.2" 45 = 45.4"	w/DMX on board	R3 = RGBW (3K) R4 = RGBW (4K)	GE = General/Diffused		(wired as non-dim) OT96-JBX	E99216 E89190 E98437 E98149 E89188 E89365 E89186
			57 = 57.2"	19 RDMX = 19W / Remote w/DMX on board					E98493 E98994 E98993 E89187

¹See page 2




Housings & fixing systems Order separately, see pages 3-6






inter•lux





45.4" 13W



DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010*

Osram, 96W, 120/277VAC-24VDC, supplied in a Dry location enclosure. Wired as nondim. DMX Control not included/ order separately.

OT96-JBX

Osram, 96W Non-dim 120/277VAC-24VDC, Wet location DMX Control not included/ order separately.

DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010* Osram, 96W, 120/277VAC-24VDC, supplied in a Dry location enclosure. Wired as nondim.


DMX Control not included/

order separately.

OT96-JBX

Osram, 96W Non-dim 120/277VAC-24VDC, Wet location DMX Control not included/ order separately.

57.2" 19W



DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010* Osram, 96W, 120/277VAC-24VDC, supplied in a Dry location enclosure. Wired as nondim. DMX Control not included/ order separately. OT96-JBX Osram, 96W Non-dim 120/277VAC-24VDC, Wet location DMX Control not included/ order separately.

Cables (*one Power feed cable, one DMX feed cable and one DMX terminator required)

E99216*	E89190*	E98437	E98149	E89188	E89365*
59" line volt. power feed cable F 4 pin M12	196" low volt. power feed cable F 4 pin M12	39" low volt. power extension cable M+F 4 pin M12	196" low volt. power extension cable M+F 4 pin M12	393" low volt. power extension cable M+F 4 pin M12	DMX Terminator
E89186*	E98493*	E98994	E98993	E89187	
196" DMX cable M 5 pin M12 + M 3 pin XLR	196" DMX cable M 5 pin M12 + M 5 pin XLR	39" DMX extension 0-10V M+F 5 pin M12	196" DMX extension 0-10V M+F 5 pin M12	393" DMX extension 0-10V M+F 5 pin M12	





inter•lux

Paseo | Floor with trim outer housing



1.9	
0.9	

		Outer housing	Cable gland
Anod. Al.	20.2 in x Paseo 20.2 in	E98355	E98471
Anod. Al.	22.7 in x Paseo 22.7 in	E98430	E98472
Anod. Al.	45.4 in x Paseo 45.4 in	E98356	E98473
Anod. Al.	57.2 in x Paseo 57.2 in	E98357	E98474



Installation accessories



Paseo | Floor trimless / Surface mount outer housing






1.9

0.9

		Outer housing	Cable gland
Anod. Al.	20.2 in x Paseo 20.2 in	E98467	E98471
Anod. Al.	22.7 in x Paseo 22.7 in	E98468	E98472
Anod. Al.	45.4 in x Paseo 45.4 in	E98469	E98473
Anod. Al.	57.2 in x Paseo 57.2 in	E98470	E98474



Installation accessories








inter•lux

Paseo | Ceiling with trim outer housing





Anod. Al.	20.2 in x Paseo 20.2 in	E98374
Anod. Al.	22.7 in x Paseo 22.7 in	E98435
Anod. Al.	45.4 in x Paseo 45.4 in	E98375
Anod. Al.	57.2 in x Paseo 57.2 in	E98376




Installation accessories



Paseo | Ceiling trimless outer housing





Anod. AL. 20.2 in x Paseo 20.2 in	E98367
Anod. Al. 22.7 in x Paseo 22.7 in	E98434
Anod. Al. 45.4 in x Paseo 45.4 in	E98368
Anod. Al. 57.2 in x Paseo 57.2 in	E98369



Installation accessories









inter•lux

Paseo | Surface 3D outer housing





Anod. Al. 20.2 in x Paseo 20.2 in	E98836
Anod. AL 22.7 in x Paseo 22.7 in	E98839
Anod. AL 45.4 in x Paseo 45.4 in	E98837
Anod. AL 57.2 in x Paseo 57.2 in	E98838



Installation accessories




Paseo | Surface adjustable outer housing



2.9		
	3.3	

Anod. Al. 20.4 in x Paseo 20.2 in	E98842
Anod. Al. 22.9 in x Paseo 22.7 in	E98843
Anod. Al. 45.6 in x Paseo 45.4 in	E98844
Anod. Al. 57.4 in x Paseo 57.2 in	E98845



Installation accessories








inter•lux


Paseo | Adjustable mounting clips





Mounting plate for uneven horizontal surfaces

(ordered separately)



0.1

E98771

Pair of fastening clips made of transparent polycarbonate to install the fixture in an even horizontal mounting surface. A directional accessory that allows Paseo tilt movement from + 90° to -90°.


L inches		L1 inches
11.8 in	7.9 in	E98772
Plate for 20.2 or 20.7" Paseo fixtures		
L inches		L1 inches
37.4 in	33.5 in	E98773
Plate for45.4 or 57.2" Paseo fixtures		

The plate, without fixing it to the surface, can be used as a mobile support for the adjustable clips and fixture. Clips not included in codes E98772 - E98773 (ordered separately)

Paseo | Extraction key







E98475

The Paseo extraction key (ordered separately) allows its removal from the outer housing. Compatible with all Paseo outer housings.



