



**General:** Suelo is a family of round LED in-grades that includes a broad selection of specialty optics in multiple sizes and outputs, making it possible to find the perfect luminaire to illuminate outdoor architectural elements such as facades, columns as well as landscape and pathway lighting within the same product range.

The standard Suelo R provides maximum output and a selection of accessories to control the emission based on application needs. The Suelo PRO version has a more recessed optical chamber instead, to guarantee the best glare control without the need of any louver.

Lastly, Suelo is also available with a Dual Optic (Double, allowing to aim light at two different areas from one fixture) and in a Telescopic version, with an adjustable aluminum tube that elevates the fixture off the ground, to prevent growing vegetation from blocking the light.

**Fixture Body:** Anodized aluminum 6026.

**Trim:** Semi-Flush Stainless-Steel Trim with Frosted glass.

**Mounting/Casing:** Black, ABS casings for Concrete installations.

**Drive-over:** Up to 5,511 lbs.

**Dimensions/Weight:** 2.0" (0.35 lbs)

**Driver:** Remote, 120-277V Dimmable 0-10V or Non-Dim. Available in both Constant Current (CC) and Constant Voltage (CV) to leave flexibility of installation.

**CC features:** Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

**CV features:** Possibility to use higher wattage drivers and feed multiple fixtures with less drivers; fixtures need to be wired in parallel.

**Wattages:** 2W (2.0")

**Cable:** Fixture comes with 3.28' of power cable and built-in Aquastop® (anti-wicking) system

**IP rating:** IP67 for temporary submersion up to 3.3' of depth for up to a maximum of 1 hr.

**IK rating:** IK 09

**ETL Certification:** ETL, wet location

**Optic:** Fixed, Frosted.

**Color temperatures:** 2700K – 3000K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.0" (2W)

| Delivered Lumens* | 2.0" |
|-------------------|------|
| GE                | 17   |

\*Values shown for 3000K

| Ordering Information |  |                    |           |  |  |                       | (Required) <sup>1</sup> |         |  |
|----------------------|--|--------------------|-----------|--|--|-----------------------|-------------------------|---------|--|
| Product              | Trim   | Type               | Diameter  | Wattage/Operation  | Color Temp                             | Optic                 | +                       | Housing | Driver   |
| SUP = Suelo PRO      | SFSTVR = Semi-Flush St. Steel Vandal Resistant | FR = Fixed Frosted | 20 = 2.0" | 2 CC = 2W / Constant Current (630mA)<br>2 CV = 2W / Constant Voltage (24VDC) | 27 = 2700K<br>30 = 3000K<br>40 = 4000K | GE = General Illumin. |                         | E99685  | <b>CC:</b><br>ECO30W-630<br>SOLO50W-630<br>SOLO100W-630<br><b>CV:</b><br>OT96-D010<br>OT96-JBX |

<sup>1</sup> See page 2

## 2.0" 2W

### Housing

#### E99685

Recessed Housings



### DRIVER OPTIONS (pick one)

#### C.C. Power supply options (remote only)

##### ECO30W-630

0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

##### SOLO50W-630

0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures

##### SOLO100W-630

0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures

#### C.V. Power supply options (remote only)

##### OT96-D010

Osram, 10% 0-10V dim, 96W,  
24VDC, 120-277VAC, supplied  
in a Dry location enclosure

##### OT96-JBX

Osram, Non-dim 24VDC,  
120-277VAC, Wet location