


# Xenia Wall Frosted – Remote Driver

## XE-W-FR-...-CV-GE...

Delivered Lumens - General Illumination

		Length [Wattage]				
		14 [7 CV]	25 [13 CV]	37 [20 CV]	48 [26 CV]	60 [33 CV]
CCT	27-	156	312	438	584	730
	30-	163	326	459	612	765
	35-	163	326	459	612	765
	40-	165	331	466	621	801
Polar Plot / Cone Of Light Multiplier						
		14 [7 CV]	25 [13 CV]	37 [20 CV]	48 [26 CV]	60 [33 CV]
		0.27	0.53	0.75	1.00	1.25



Beam Angle (0-180) = 115.2  
 Beam Angle (90-270) = 128.4

## CONE OF LIGHT - 27.8W 3000K

General Illumination

XE-W-FR-48-26-CV-30-GE'

Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Width [Ft]
20	0	63.0
18	1	56.7
16	1	50.4
14	1	44.1
12	1	37.8
10	2	31.5
8	3	25.2
6	5	18.9
4	12	12.6
2	49	6.3

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.