

Archiline Pro Stainless Steel Frame RGBW

interlux



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm), Aluminum finish
Trim: 316 Marine Grade Stainless Steel, Brushed. Extra clear glass - Tempered
Mounting/Housing: Galvanized Steel (required for in ground installations).
Drive-over: Walk-Over only.
Dimensions/Weight: 23" (12.13 lbs) – 42.9" (24.25 lbs)

Driver: Integral, 120-277V + DMX interface.
Wattages: 44W (23") – 86W (42.9")
Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).
Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood – Elliptic.
Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



23" (44W)
42.9" (86W)


Nominal Lumens RGB/RGBW	23"	42.9"
Red	405	702
Green	783	1404
Blue	126	216
White 3K/4K	711 / 891	1260 / 1566

Ordering Information									
ARP	RSF	FDL			IDMX			+	
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic		Housing (Required) ¹
ARP = Archiline	RSF = Recessed Stainless Steel Frame	FDL = Fixed DarkLight	23 = 23"	44 = 44W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	NSP = Narrow Spot SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer	E98771 (23) E99830 (43)	
			43 = 42.9"	86 = 86W					Cables ¹
									E98660 E98661 E98662 E98663 E98986

¹ See page 2



23" 44W IDMX




HOUSING

E99771
Outer Housing



42.9" 86W IDMX



HOUSING

E99830
Outer Housing



Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4" feed cable all in one power + DMX M+F 6 pin shield	196.9" feed cable all in one power + DMX M+F 6 pin shield	39.4" extension all in one power + DMX M+F 6 pin shield	196.9" extension all in one power + DMX M+F 6 pin shield	DMX 1200 terminator