



**General:** Beriel is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

**Fixture Body:** Brass (Chromium Plated).

**Diffuser:** Clear Glass.

**Trim:** Bezel.

**Mounting:** Semi-Recessed ceiling.

**Dimensions/Weight:** 0.8" (0.13 lbs)

**Driver:** Remote, DMX 120-277V Dimmable.

**Operation:** Constant Current (CC).

**Wattages:** 2.1W (0.8")

**Cable:** Fixture comes with 0.39' of power cable.

**IP rating:** IP20. Fixture is protected against solid objects greater than 0.04". Not suitable for Outdoor applications or any contact with water.

**ETL Certification:** ETL, dry location

**Optics:** Fixed, General distribution.

**Color temperatures:** 2700K – 3000K – 4000K – 5000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (1W CC)

0.8" (1.5W CC)


| Delivered Lumens* | 0.8" [1 CC] | 0.8" [1.5 CC] |
|-------------------|-------------|---------------|
| GE                | 96          | 96            |

\*Values shown for 3000K

| Ordering Information |                          |   |           |  |  |                           | (Required) |                              |   |
|----------------------|--------------------------|---|-----------|--|--|---------------------------|------------|------------------------------|---|
| Product              | Trim/Film                | Type  | Diameter  | Wattage/Operation  | Color Temp   | Optic                     | +          | Housing <sup>1</sup>         | Driver <sup>1</sup>                       |
| BRL = Beriel         | SFCH = Semi-Flush Chrome | D = Diamond Shaped Crystal<br>G = Globe Shaped Crystal<br>CO = Cone Shaped Crystal<br>UCO = Upside Down Cone Shaped Crystal | 08 = 0.8" | 1 CC = 1W / Constant Current (350mA)<br>1.5 CC = 1.5W / Constant Current (500mA) | 27 = 2700K<br>30 = 3000K<br>40 = 4000K<br>50 = 5000K | GE = General distribution |            | E84335 (1W)<br>E84917 (1.5W) | ECO30W-XXX<br>SOLO50W-XXX<br>SOLO100W-XXX |

<sup>1</sup> See page 2

## 0.8" 1W CC



## Housing

**E84335**  
Recessed Housing



## DRIVER OPTIONS (pick one)

### C.C. Power supply options (remote only)

**ECO30W-500**

0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures


**SOLO50W-500**

0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtures

**SOLO100W-500**

0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtures

## 0.8" 1.5W CC



## Housing

**E84917**  
Recessed Housing



## DRIVER OPTIONS (pick one)

### C.C. Power supply options (remote only)

**ECO30W-500**

0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-500**

0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtures

**SOLO100W-500**

0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtures