


Eyelet65

ROUND


EY65-RWH-F-....-SP...		
Delivered Lumens - Spot		
		Size [Wattage]
		12 [2 CC]
CCT	27-	161
	30-	170
	40-	182
		Polar Plot / Cone Of Light Multiplier
		12 [2 CC]
		1.00



Beam Angle (0-180) = 18.4
Beam Angle (90-270) = 23.0

CONE OF LIGHT - 2W 3000K Spot EY65-RWH-F-12-2-CC-30-SP*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	2	6.5
18	2	5.8
16	3	5.2
14	3	4.5
12	5	3.9
10	7	3.2
8	11	2.6
6	19	1.9
4	42	1.3
2	169	0.6


EY65-RWH-F-....-FL...		
Delivered Lumens - Flood		
		Size [Wattage]
		12 [2 CC]
CCT	27-	152
	30-	171
	40-	183
		Polar Plot / Cone Of Light Multiplier
		12 [2 CC]
		1.00



Beam Angle (0-180) = 27.0
Beam Angle (90-270) = 28.8

CONE OF LIGHT - 2W 3000K Flood EY65-RWH-F-12-2-CC-30-FL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	1	9.6
18	1	8.6
16	2	7.7
14	2	6.7
12	3	5.8
10	4	4.8
8	7	3.8
6	12	2.9
4	26	1.9
2	106	1.0

EY65-RWH-F-....-WFL...		
Delivered Lumens - Wide Flood		
		Size [Wattage]
		12 [2 CC]
CCT	27-	147
	30-	160
	40-	171
		Polar Plot / Cone Of Light Multiplier
		12 [2 CC]
		1.00




Beam Angle (0-180) = 62.8
Beam Angle (90-270) = 65.2

CONE OF LIGHT - 2W 3000K Wide Flood EY65-RWH-F-12-2-CC-30-WFL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	0	24.4
18	0	22.0
16	1	19.5
14	1	17.1
12	1	14.6
10	1	12.2
8	2	9.8
6	4	7.3
4	9	4.9
2	34	2.4

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.


EY65-SWH-F-....SP...		
Delivered Lumens - Spot		
		Size [Wattage]
		13 [2 CC]
CCT	27-	181
	30-	153
	40-	164
		Polar Plot / Cone Of Light Multiplier
		13 [2 CC]
		1.00



Beam Angle (0-180) = 18.4
Beam Angle (90-270) = 23.0

CONE OF LIGHT - 2W 3000K Spot EY65-SWH-F-13-2-CC-30-SP*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	2	6.5
18	2	5.8
16	3	5.2
14	3	4.5
12	5	3.9
10	7	3.2
8	11	2.6
6	19	1.9
4	42	1.3
2	169	0.6


EY65-SWH-F-....FL...		
Delivered Lumens - Flood		
		Size [Wattage]
		13 [2 CC]
CCT	27-	172
	30-	154
	40-	165
		Polar Plot / Cone Of Light Multiplier
		13 [2 CC]
		1.00



Beam Angle (0-180) = 27.0
Beam Angle (90-270) = 28.8

CONE OF LIGHT - 2W 3000K Flood EY65-SWH-F-13-2-CC-30-FL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	1	9.6
18	1	8.6
16	2	7.7
14	2	6.7
12	3	5.8
10	4	4.8
8	7	3.8
6	12	2.9
4	26	1.9
2	106	1.0

EY65-SWH-F-....WFL...		
Delivered Lumens - Wide Flood		
		Size [Wattage]
		13 [2 CC]
CCT	27-	170
	30-	144
	40-	154
		Polar Plot / Cone Of Light Multiplier
		13 [2 CC]
		1.00



Beam Angle (0-180) = 62.8
Beam Angle (90-270) = 65.2

CONE OF LIGHT - 2W 3000K Wide Flood EY65-SWH-F-13-2-CC-30-WFL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	0	24.4
18	0	22.0
16	1	19.5
14	1	17.1
12	1	14.6
10	1	12.2
8	2	9.8
6	4	7.3
4	9	4.9
2	34	2.4

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.