



General: With its microscopic 1.2"/1.3" size, Eyelet65 fully integrates in any landscape application, providing a powerful and yet discrete illumination of small planters and trees. Eyelet is available in multiple optics, with a snoot accessory to shape the beam, and can be installed in different ways.

Fixture Body: Open-pore Anodized and Powder Coated Aluminum.

Glass: Extra-clear glass.

Bracket: Anodized Aluminum Bracket, Black Painted. Bracket pivots up to 180° on the vertical plane (no horizontal plane adjustment).

Mounting details: Fixture can be installed straight onto a surface or by using any of the mounting pegs available.

Dimensions/Weight: 1.2" round, 1.3" square (0.35 lbs)

Driver: Remote, 120-277V Dimmable 0-10V.

Wattage: 2W

Cable: Fixture comes with 3.28' of power cable.

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 03

ETL Certification: ETL, wet location

Optics: Fixed. Available in Spot – Flood – Wide Flood. Snoot accessory available.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.2" (2W) RWH



1.3" (2W) SWH

Delivered Lumens*	1.2"/1.3"
SP	170
FL	171
WFL	160


*Values shown for 3000K

Ordering Information

EY65		F		2 - CC					
Product	Trim/Finish	Type	Size	Wattage/Operation	Color Temp	Optic	+	Accessories ¹	Driver (Required) ¹
EY65 = Eyelet65	RWH = Round White RBL = Round Black RGR = Round Gray	F = Fixed	12 = 1.2" round	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	SP = Spot FL = Flood WFL = Wide Flood		Peg E98624 E98669 Snoot E83359 W-U300001 E84992	ECO30W-630 SOL050W-630 SOL0100W-630
	SWH = Square White SBL = Square Black SGR = Square Gray		13 = 1.3" square						

¹ See page 2

1.2" 2W 630mA ROUND




DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

1.3" 2W 630mA SQUARE



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

ACCESSORIES



E98624

Steel Peg
6.3" length



E98669

Peg
3.98" length



E83359

Round Snoot
1.2"ø x 0.9"



W-U300001

Square Snoot
1.2"sq. x 0.9"/0.3"



E84992

Spanner, to
install snoot



Eyelet65 with round
snoot (E83359)



Eyelet65 with square
snoot (W-U300001)