



Order Code	G-Cat.module.accessory.finish
Example	G-Cat.XTM,3000K,1300lm.bulb.black

- Materials: Aluminum
- Light source: Xicato XIM 0.4" LES or 0.7" LES LED module or Lumenetix LED module
- CRI Ra: ≥80 or ≥95 Artist Series
- IP Rating: IP66
- Finish: Anodized or painted any RAL color
- Dimming:
 - XTM 0-10V
 - XIM 0-10V, DALI or Wireless
 - Lumenetix: DMX
- Supply:
 - XTM Constant current integral driver
 - XIM 48V or 240V to integral PSU
 - Lumenetix 240V to integral driver
- Weight: 4.4Lb
- Description: The G-Cat is a versatile, decorative yet functional, robust wire mounted IP66 rated down lighter. It can be mounted to Ø0.3" catenary wire using a locking hinge mechanism or via a direct single suspension. Since its inception we have adapted its core to accept many custom (recycled and recyclable) acrylic fronts, optics, lenses and even patterned shades.
- Accessories: Lower section machined from solid acrylic
Option with Ø2.8" optics also available



Dimensions (Max Power)	Xicato XTM Non Dim or 0-10V (Initial Output*)	XTM Remote	XIM 0-10 or DALI	Lumenetix DMX
Heatsink Ø4" x 4" Acrylic 4" (18W)	(80CRI 2100lm) (95 CRI 1400lm)	(80CRI 2100lm) (95 CRI 1400lm)	(80CRI 1300lm) (95 CRI 1300lm)	(95 CRI 1000lm)



Heatsink Ø4" x 4" Acrylic 4" max (18W)	(80CRI 2100lm) (95 CRI 1400lm)	(80CRI 2100lm) (95 CRI 1400lm)	(80CRI 1300lm) (95 CRI 1300lm)	(95 CRI 1000lm)
--	-----------------------------------	-----------------------------------	-----------------------------------	-----------------



Heatsink Ø4" x 4" Bezel Ø4" x 1.6" (18W)	(80CRI 1300lm) (95 CRI 930lm)	(80CRI 1300lm) (95 CRI 930lm)	(80CRI 1300lm) (95 CRI 700lm)	(95 CRI 750lm)
--	----------------------------------	----------------------------------	----------------------------------	----------------



	Type L (Initial Input*)
Heatsink/ Lamptube Ø2.4" x 4" (6.6W)	(95 CRI 560lm)



Heatsink Ø1.8" x 2.6" Acrylic Orb Ø4" (6.6W)	(95 CRI 560lm)
--	----------------



Heatsink Ø1.8" x 2.6" Shade Ø11.8" (6.6W)	(95 CRI 560lm)
---	----------------