

Periskop 4.3" Optics



General: The Periskop outdoor family of flood lights represents a versatile landscaping solution for trees, bushes, sculptures, as well as building facades. Periskop is available in multiple sizes and optics (including a Narrow Spot beam for dramatic effects), with multiple installation solutions available and a selection of accessories to control and shape the beam to your desire.

Fixture Body: Open-pore Anodized and Powder Coated Die-Cast Aluminum.

Glass: Extra-clear Tempered glass.

Bracket: Powder Coated Steel Bracket, Black Painted. Bracket pivots -10°/+60° on the vertical plane and swivels +/-43.5° on the horizontal plane.

Mounting details: Fixture can be installed straight into concrete or onto different surfaces by using one of the several mounting accessories available within the family.

Dimensions/Weight: 4.3" (3.31 lbs)

Driver: Integral, 120-277VAC Dimmable 0-10V.

Wattage: 20W (4.3")

Cable: Fixture comes with 3.28' of power cable and it's equipped with TCS safety system to shield circuits from moisture.

IP rating: IP66 for protection against dust and water jets from any angle.

IK rating: IK 10 (4.3")

ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood. Standard Visors and Snoots accessories available. Honeycomb louvers and Elliptic lenses available upon request.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers



4.3" (20W) Fixed



4.3" (20W) Narrow

Delivered Lumens*	4.3"
NSP	1453
SP	1921
FL	1819
WFL	1816

*Values shown for 3000K

Ordering Information

Product	Trim/Finish	Type	Size	Wattage/Operation	Color Temp	Optic	+	Accessories ³
PER = Periskop	SWH = Square White SBL = Square Black SGR = Square Gray SDB = Square Dark Brown	F = Fixed N = Narrow beam ¹	43 = 4.3"	20 ID = 20W / Integral Driver (0-10V Dim)	27 = 2700K 30 = 3000K 40 = 4000K	NSP = Narrow Spot ² SP = Spot FL = Flood WFL = Wide Flood		Peg E98549 Tree belt E99802 Anti-glare E98967 E98970 ⁴


¹ Available with NSP ONLY

² Available with N ONLY


³ See page 2

⁴ Available with F ONLY







4.3" 20W



HORIZONTAL PIVOTING BRACKET



ACCESSORIES

					
E98549	E99802	E98967	E98970	On request	On request
8" Peg for soft ground	Tree belt For trees max diameter of 39"	Anti-glare Visor	Anti-glare Snoot (Fixed ONLY)	Anti-glare louver (Fixed ONLY)	Ellipical filter (Fixed ONLY)