

Periskop 6.4" Optics



General: The Periskop outdoor family of flood lights represents a versatile landscaping solution for trees, bushes, sculptures, as well as building facades. Periskop is available in multiple sizes and optics (including a Narrow Spot beam for dramatic effects), with multiple installation solutions available and a selection of accessories to control and shape the beam to your desire.

Fixture Body: Open-pore Anodized and Powder Coated Die-Cast Aluminum.

Glass: Extra-clear Tempered glass.

Bracket: Powder Coated Steel Bracket, Black Painted. Bracket pivots -10°/+60° on the vertical plane and swivels +/-43.5° on the horizontal plane.

Mounting details: Fixture can be installed straight into concrete or onto different surfaces by using one of the several mounting accessories available within the family.

Dimensions/Weight: 6.4" (8.82 lbs)

Driver: Integral, 120-277VAC Dimmable 0-10V.

Wattage: 33W & 50W (6.4")

Cable: Fixture comes with 3.28' of power cable and it's equipped with TCS safety system to shield circuits from moisture.

IP rating: IP66 for protection against dust and water jets from any angle.

IK rating: IK 09 (6.4")

ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Spot – Narrow Flood – Flood – Wide Flood. Standard Visors and Snoots accessories available. Honeycomb louvers and Elliptic lenses available upon request.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



6.4" (33W / 50W) Fixed



6.4" (50W) Narrow

Delivered Lumens*	6.4" / 33W	6.4" / 50W
NSP	N/A	3076
NFL	3491	4929
FL	3502	4539
WFL	3382	4949

*Values shown for 3000K

Ordering Information							
PER							
Product	Trim/Finish	Type	Size	Wattage/Operation	Color Temp	Optic	+ Accessories ³
PER = Periskop	SWH = Square White SBL = Square Black SGR = Square Gray SDB = Square Dark Brown	F = Fixed	64 = 6.4"	33 ID = 33W / Integral Driver (0-10V Dim) ¹ 50 ID = 50W / Integral Driver (0-10V Dim)	27 = 2700K 30 = 3000K 40 = 4000K	NFL = Narrow Flood ¹ FL = Flood ¹ WFL = Wide Flood ¹	Peg E98549 Tree belt E99802 Anti-glare E98967 E98970 ⁴
		N = Narrow beam	64 = 6.4"	50 ID = 50W / Integral Driver (0-10V Dim)	27 = 2700K 30 = 3000K 40 = 4000K	NSP = Narrow Spot ²	

¹ Available with F ONLY


² Available with N ONLY

³ See page 2


⁴ Available with F ONLY



6.4" 33W / 50W



HORIZONTAL PIVOTING BRACKET



ACCESSORIES



E98549
8" Peg for
soft ground



E99802
Tree belt
For trees max
diameter of 39"



E98967
Anti-glare Visor



E98970
Anti-glare Snoot
(Fixed ONLY)



On request
Anti-glare
louwer
(Fixed ONLY)



On request
Ellipical filter
(Fixed ONLY)