




20 Linear Mini Edgeless Cove


- Extremely small knife-edge cove utilizing the 20Linear for general indirect distribution.
- Continuous mounting to any desired length.
- Luminaire has opal or satin diffuser options for even illumination, elimination of glare and high efficiency.
- Lengths and angles factory cut to exact field dimensions - housing may be field cut.
- Removable light source sub assembly for ease of installation and maintenance.
- High efficiency linear LED in a range of outputs, including static white, tunable white, warm dim and RGBW.
- Mini size requires remote driver.
- Lengths and angles factory cut to exact field dimensions.
- Mitered corners available with continuous illumination.
- Made in the USA.



Housing	Precision extruded aluminum for true dimensions and tolerances Alignment hardware for invisible seam from below Housing provided in any exact length, or field cut Snap-in LED insert for easy installation Standard and tailored lengths Corners: standard and non-standard Finishes: RAL 9010 white 15% gloss
Integration	Seamless, architectural integration into gypsum for minimal visual detail and true knife edge
Distribution	Wide indirect distribution fully illuminates the cove and redirects light into the adjacent space
LED	>90 CRI, 3-Step MacAdam, 2700-4000K static white 1.5W - 15W per foot, 180 nominal lumens per watt average, constant current Tuneable white 2200-4000K, 80 nominal lumens per watt average Warm Dim to emulate incandescent when dimming; 75 nominal lumens per watt average RGBW, 50 nominal lumens per watt L70 (TM21 Projected 85C) Static White / Tunable White = 72,000 hours, RGBW = 50,000 hours, WD = 36,000 hours
Lens	SD - satin clear dust cover for wipe down applications OD - Opal diffuser provides even, continuous line of light and general illumination
Driver	Remote driver Compatible with quality constant current (Static White / Tunable White) and constant voltage (WD / RGBW) drivers
Connectivity	POE Wireless
Weight	1lb per foot
Operating Temp	Suitable for operation in maximum ambient temperature of 35C (95F)
Warranty	5-year Limited (see complete company warranty information)
Certifications	ETL and ETL-C for dry and damp location, CE
Voltages	Low Voltage Fixture, 120-277VAC Driver (remote)



Lenses/Accessories



20 Linear Mini Edgeless Cove

Model	Fixation	Pattern	Length	Power ³	CRI/CCT ⁴	Driver ⁶	Lens	Finish ⁷	Options
WG-20MEC	RPT	S ¹ PC ² PR ² PPI ² PPO ² PZ ²	A A x B A x B x C A x B x A x B	P0 P1 P2 P3 L M H	927 930 935 940 TW ⁵ WD RGBW	E1 L1 POE BT DALI TQ D010 L3DAE L3DOE EL96 DMX	SD (std) OD	W (std) F	CDC EM

- Model**
- WG-20MEC = 20 Linear Mini Edgeless Cove
- Fixation**
- RPT = Recessed plaster trim
- Pattern**
- S = Straight run¹
 - PC = Standard patterns coffer 2, 3 or 4 sided with 90° inside corners²
 - PR = Standard patterns raft 2, 3 or 4 sided with 90° outside corners²
 - PPI = Wall to wall / wall to ceiling, 90° inside corner²
 - PPO = Wall to wall / wall to ceiling, 90° outside corner²
 - PZ = Non-standard patterns and/or corners other than 90°; consult factory²
- Length**
- A, B, C = specify inches to the nearest 0.25" (i.e. 72.25")
For patterns specify each length (i.e. 2 sided: A x B = 72.25" x 48"; 3 sided: A x B x C; 4 sided: A x B x A x B)

- Power³**
- P0 = 1.5 W/ft
 - P1 = 3 W/ft
 - P2 = 6 W/ft
 - P3 = 10 W/ft
 - L = 2.7 W/ft WD low power (24V)
 - M = 5.5 W/ft WD medium power (24V) [RGBW 7.6 W/ft]
 - H = 8W/ft WD high power (24V)

- CRI/CCT** (90+ CRI minimum)⁴
- 927 = 2700K
 - 930 = 3000K
 - 935 = 3500K
 - 940 = 4000K
 - TW = Tunable White 2200K - 4000K⁵
 - WD = Warm Dim 1800K-3000K
 - RGBW = 3000K White

- Driver (remote)⁵**
- E1 = eldoLED 0.1% dimming, 0-10V (120-277V)
 - L1 = Lutron 1% dimming, EcoSystem (120-277V)
 - POE = Power over Ethernet
 - BT = Wireless CAS - Casambi (Must specify BT with E1 or DALI)
 - DALI = eldoLED DALI DT8 0.1% (120-277V)
 - TQ = T-series for Lutron Quantum 0.1 % (120-277V) [TW only]
 - D010 = Osram, 10%, 0-10V dimming, 120-277V [WD only]
 - L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V [WD only]
 - L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V (remote) [WD only]
 - DMX = Osram + eldoLED 24V, DMX dimming [WD + RGBW Only]

- Lens**
- SD = Satin clear diffuser (standard)
 - OD = Satin opal diffuser

- Finish⁶**
- W = White, 15% gloss, RAL 9010 / Tiger Drylac 009/10120 (standard)
 - F = Custom finish, specify RAL

- Options**
- CDC = Clear dust cover
 - EM = Emergency (remote)

Whitegoods reserves the right to change any information without prior notice.

Notes

- 1 Standard setup assumes the cove ends at a perpendicular wall and the LED board is setback from the end to minimize light on the perpendicular wall. Contact us for options.
- 2 See pattern specsheet.
- 3 Wattage shown does not include power supplies/drivers.
- 4 Refer to specsheet for delivered lumen data for all product configurations.
- 5 TW offered up to P3 (10W/ft) power level.
- 6 See power supply page for details.
- 7 See Tiger Drylac color chart: inter-lux.com/tiger.

