


20 Linear Mini Z Cove

WG-20MZC-...-OD-W

Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	174	348	609	-
	930	190	379	662	-
	935	225	450	787	-
	940	267	534	935	-
	WD ²	133	277	400	-
	RGBW ³	-	-	-	226
UGR ⁴		27.2	29.7	31.5	-



BEAM ANGLE (0-180) = 81.8
BEAM ANGLE (90-270) = 116.3

ILLUMINANCE - 48" OD H 3500K


WG-20MZC-...-S-48-H-935-...-OD-W...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	296	3.5
4	74	6.9
6	33	10.4
8	19	13.9
10	12	17.3
12	8	20.8
14	6	24.3
16	5	27.7
18	4	31.2
20	3	34.7

WG-20MZC-...-SD-W

Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	248	495	867	-
	930	270	539	942	-
	935	320	640	1120	-
	940	380	760	1331	-
	WD ²	190	394	570	-
	RGBW ³	-	-	-	322
UGR ⁴		29	31.6	33.4	-



BEAM ANGLE (0-180) = 62.4
BEAM ANGLE (90-270) = 106.6

ILLUMINANCE - 48" SD H 3500K

WG-20MZC-...-S-48-H-935-...-SD-W...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	537	2.4
4	134	4.8
6	60	7.3
8	34	9.7
10	21	12.1
12	15	14.5
14	11	16.9
16	8	19.4
18	7	21.8
20	5	24.2

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	-
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.