


Solar Powered Outdoor Accent Light
Automatic Operation

piek mini solar join	color	item no.	system performance	
	 anthracite RAL 7016	93076-AN-JO	4 W/240 lm 1x piek mini solar join	1 W/60 lm 4x piek mini solar join
	 cool brown	93076-CB-JO	4 W/240 lm 1x piek mini solar join	1 W/60 lm 4x piek mini solar join
	 deep black RAL 9005	93076-BL-JO	4 W/240 lm 1x piek mini solar join	1 W/60 lm 4x piek mini solar join

requires solar join system see page 2

technical information:
LED
lithium-ion solar rechargeable battery
1x 2600 mAh
2700K
solar panel

reflector: flood

operating time:
automatic switch-on at dusk
for a duration of approx. 5 hrs

location:
with permanent direct sunlight
(possibly limited function,
due to regionally conditioned
longer shading, e.g. in winter
months)

solar join connection:
3.3 ft supply cable (H05RN8–F 2x0.03"²)
including solar join plug

movable

material:
head: aluminum die-casting
powder-coated
pole: stainless steel
powder-coated
clear glass

protection class:
IP65

light direction:
(◉)

mounting:
spike mount into soil or sod




Auto mode, automatically turns on at dusk
and turns off 5 hours later

IP44.DE solar join offers very different solar luminaires with piek mini solar, reed solar and lix spike solar. They can be used in any combination with IP44.DE solar join.



required accessory

solar panel L




solar panel
lithium-ion battery
4x 2600 mAh
3.3 ft supply cable (H05RN8-F 2x0.03"²)
including solar join plug)
protection class: IP65

powers up to any 4 solar join fixtures

color	item no.
 anthracite RAL 7016	53110-AN
 cool brown	53110-CB
 deep black RAL 9005	53110-BL


optional accessory



extension cable

solar join plug on solar join socket
cable: H05RN8-F 2x0.03"²
protection class: IP68

6.6 ft	53102
13.1 ft	53104
26.2 ft	53108



junction

1x solar join plug; 2x/3x/4x solar join socket
cable: H05RN8-F 2x0.03"²
protection class: IP68

port 2	53122
port 3	53123
port 4	53124