



Aline 70

PENDANT

Direct or direct-indirect illumination

Model 1550

Type

P Pendant

Size

48 49.1" (1246mm)
60 60.9" (1547mm)
72 72.8" (1848mm)
84 84.6" (2149mm)
Custom

Wattage^{1,2}

Direct

48"
LD 12W (1600lm)
MD 24W (2970lm)

Indirect³

LI 12W (1600lm)
MI 24W (2970lm)

60"

LD 15W (2000lm)
MD 30W (3715lm)
72"

LI 15W (2000lm)
MI 30W (3715lm)

LD 18W (2400lm)
MD 36W (4460lm)

LI 18W (2400lm)
MI 36W (4460lm)

84"

LD 21W (2800lm)
MD 42W (5200lm)

LI 21W (2800lm)
MI 42W (5200lm)

XI-No Indirect

Color Temp⁴

30 3000
35 3500
40 4000

Voltage

U 120/277 Volt

Driver

RD Remote

Control - RD

S Non-dim
D010 0-10V 10%
L3DAE Lutron Hi-lume 1% EcoSystem
L3DOE Hi-lume Premier 0.1% EcoSystem

Diffuser Bottom

SW Satin opal acrylic

Diffuser Top

SA Satin clear acrylic
CT Aluminum-painted to match the fixture

Finish⁵

16 Clear anodized aluminum
21 Painted white - RAL 9010 matte
26 Painted black - RAL 9005 matte
22 Painted custom color

Mounting

SC Straight cables

Circuit

CS Circuit - Single
CD Circuit - Dual

Power Cable^{6,2}

CC Clear insulated cable (standard)
WC White cable
BC Black cable

Notes

- 1 Nominal lumens value specified
- 2 Linear LED board, constant voltage 24 Volt
- 3 For no indirect light specify XI
- 4 90+ CRI standard
- 5 Canopy finish matches housing
For Clear anodized aluminum finish, canopy finish will be painted anodized aluminum
- 6 96" standard cable length

