

Aline 70

PENDANT

Direct or direct-indirect illumination

Model 1550

Type

P Pendant

Size

48 49.1" (1246mm)
60 60.9" (1547mm)
72 72.8" (1848mm)
84 84.6" (2149mm)

Custom

Wattage^{1,2}

Direct

48"

LD 12W (1600lm)
MD 24W (2970lm)

60"

LD 15W (2000lm)
MD 30W (3715lm)
72"

LD 18W (2400lm)
MD 36W (4460lm)

84"

LD 21W (2800lm)
MD 42W (5200lm)

Indirect³

LI 12W (1600lm)
MI 24W (2970lm)

LI 15W (2000lm)
MI 30W (3715lm)

LI 18W (2400lm)
MI 36W (4460lm)

LI 21W (2800lm)
MI 42W (5200lm)

XI-No Indirect

Color Temp⁴

30 3000
35 3500
40 4000

Voltage

U 120/277 Volt

Driver

RD Remote

Control - RD

S Non-dim
D010 0-10V 10%
L3DAE Lutron Hi-lume 1% EcoSystem
L3DOE Hi-lume Premier 0.1% EcoSystem

Diffuser Bottom

SW Satin opal acrylic

Diffuser Top

SA Satin clear acrylic
CT Aluminum-painted to match the fixture

Finish⁵

16 Clear anodized aluminum
21 Painted white - RAL 9010 matte
26 Painted black - RAL 9005 matte
22 Painted custom color

Mounting

SC Straight cables

Circuit

CS Circuit - Single
CD Circuit - Dual

Power Cable^{6,2}

CC Clear insulated cable (standard)
WC White cable
BC Black cable

Notes

- 1 Nominal lumens value specified
- 2 Linear LED board, constant voltage 24 Volt
- 3 For no indirect light specify XI
- 4 90+ CRI standard
- 5 Canopy finish matches housing
For Clear anodized aluminum finish, canopy finish will be painted anodized aluminum
- 6 96" standard cable length

