



Arc 65

PENDANT

Direct, indirect or direct-indirect illumination

Model 1694¹

Type

P Pendant

Size

Specify radius
Specify length
For customized shapes, please include a layout drawing or advise desired shape

Wattage^{2,3}

Direct ⁴	Indirect ⁵
LD	LI
3 W/ft (400 lm/ft)	3 W/ft (400 lm/ft)
10 W/m (1,335 lm/m)	10 W/m (1,335 lm/m)
MD	MI
6 W/ft (743 lm/ft)	6 W/ft (743 lm/ft)
20 W/m (2,475 lm/m)	20 W/m (2,475 lm/m)

XD-No Direct XI-No Indirect

Color Temp⁶

30	3000
35	3500
40	4000

Voltage

U 120/277 Volt

Driver

RD Remote

Control - RD

S	Non-dim
D010	0-10V 10%
L3DAE	Lutron Hi-lume 1% EcoSystem
L3DOE	Lutron Hi-lume Premier 0.1% EcoSystem

Diffuser Bottom

SW	Satin opal acrylic
CB	Aluminum-painted to match the fixture

Diffuser Top

SA	Satin clear acrylic
CT	Aluminum-painted to match the fixture

Finish⁷

19	Painted anodized aluminum - RAL 9006 matte
21	Painted white - RAL 9010 matte
26	Painted black - RAL 9005 matte
22	Painted custom color

Mounting

SC Straight cables

Circuit

CS	Circuit - Single
CD	Circuit - Dual

Power Cable⁸

CC	Clear insulated cable (standard)
WC	White cable
BC	Black cable

Notes

- 1 Separately specify any downlighting elements
- 2 Nominal lumens value specified
- 3 Linear LED board, constant voltage 24 Volt
- 4 For no Direct light specify XD
- 5 For no Indirect light specify XI
- 6 90+ CRI standard
- 7 Canopy finish matches housing
- 8 96" standard cable length

