


Frame 70

inter•lux

PENDANT

Direct illumination



Model 1545


Size

24.0" (610mm)



36.0" (914mm)

48.0" (1219mm)


Custom



Straight cables with remote driver



Center canopy with remote driver



Minimum mounting height per fixture size for center canopy options:

Fixture Size (Diameter)	Minimum Mounting Height
24.0" (610mm)	15" (380mm)
36.0" (914mm)	20" (510mm)
48.0" (1219mm)	30" (760mm)




scan or click
for info




Frame 70

PENDANT

Direct illumination



Center canopy with integral driver



Minimum mounting height per fixture size for center canopy options:

Fixture Size (Diameter)	Minimum Mounting Height
24.0" (610mm)	15" (380mm)
36.0" (914mm)	20" (510mm)
48.0" (1219mm)	30" (760mm)



scan or click
for info





Frame 70

PENDANT



Direct illumination

POWER FEED / SUSPENSION





Mounting Option Power
Octagon Box (By Others)
Installed in drywall, wood or concrete ceiling

SUSPENSION - NON POWER (ACCESSIBLE CEILING)



Mounting Option - Non Power
Threaded Rod installed
to structural ceiling (By Others)

SUSPENSION - NON POWER (NON-ACCESSIBLE CEILING)



Mounting Option - Non Power
Suspension Assembly
Installed in drywall, wood or concrete ceiling



scan or click
for info