



Linea 50

PENDANT

Direct or direct-indirect illumination

Model 1672

Type	
P	Pendant

Size	
48	48.6" (1234mm)
60	60.4" (1535mm)
72	72.3" (1836mm)
84	84.1" (2137mm)
Custom	

Wattage ^{1,2}	
Direct	Indirect ³
48"	
LD 12W (1600lm)	LI 12W (1600lm)
MD 24W (2970lm)	MI 24W (2970lm)
60"	
LD 15W (2000lm)	LI 15W (2000lm)
MD 30W (3715lm)	MI 30W (3715lm)
72"	
LD 18W (2400lm)	LI 18W (2400lm)
MD 36W (4460lm)	MI 36W (4460lm)
84"	
LD 21W (2800lm)	LI 21W (2800lm)
MD 42W (5200lm)	MI 42W (5200lm)
	XI-No Indirect

Color Temp ⁴	
30	3000
35	3500
40	4000

Voltage	
U	120/277 Volt

Driver	
RD	Remote

Control - RD	
S	Non-dim
D010	0-10V 10%
L3DAE	Lutron Hi-lume 1% EcoSystem
L3DOE	Hi-lume Premier 0.1% EcoSystem

Diffuser Bottom	
SW	Satin opal acrylic

Diffuser Top	
SA	Satin clear acrylic
CT	Aluminum-painted to match the fixture

Finish ⁵	
16	Clear anodized aluminum
21	Painted white - RAL 9010 matte
26	Painted black - RAL 9005 matte
22	Painted custom color

Mounting	
PC	Power cable

Circuit	
CS	Circuit - Single
CD	Circuit - Dual

Power Cable ⁶	
CC	Clear insulated cable

- Notes**
- 1 Nominal lumens value specified
 - 2 Linear LED board, constant voltage 24 Volt
 - 3 For no Indirect light specify XI
 - 4 90+ CRI standard
 - 5 Canopy finish matches housing
For Clear anodized aluminum finish, canopy finish will be painted anodized aluminum
 - 6 96" standard power cable length

