



General: Paseo is a complete range of compact linear LED fixtures suitable to illuminate outdoor architectural elements or used as pathway lighting thanks to the new Dark version (and the already available Opaline).

Its 0.9" width makes Paseo one of the slimmest and most attractive products on the market. The new Paseo Dark adds outstanding style to the fixture when turned off, glowing to the requested color temperature when illuminated.

Fixture Body: Black, UV resistant Polycarbonate.

Mounting: Steel bracket (included).

Drive-over: Walk-Over only.

Dimensions/Weight: 23.4" (0.88 lbs) – 46.3" (1.98 lbs) – 57.8" (3.09 lbs)

Driver: Remote (120-277V, Dimmable 0-10V or Non-Dim).

Wattages: 6W (23.4") – 12W (46.3") – 15W (57.8")

Cable: Fixture comes with 0.82' of cable (Power cable required, ordered separately).

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 08

ETL Certification: ETL, wet location

Optics: Fixed, with General/Diffused distribution.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

NOTE: Paseo Dark is not compatible with other Paseo products and can only be mounted with the brackets listed in its specific product data sheet.



23.4" (6W)
46.3" (12W)
57.8" (15W)


Delivered Lumens*	23.4"	46.3"	57.8"
GE	270	540	677

*Values shown for 3000K

Ordering Information									
PA	D	OB				GE			
Product	Power	Type	Length	Wattage/operation	Color Temp	Optic	+	Drivers (Required) ¹	Brackets ¹
PA = Paseo	D = Dark	OB = Opaline Black	23 = 23.4"	6 CV = 6W / CV - Remote Const. Voltage 24VDC Driver	27 = 2700K 30 = 3000K 40 = 4000K	GE = General/ Diffused		OT96-D010 OT96-JBX	Steel Bracket (incl.) E83162 (L bracket)
			46 = 46.3"	12 CV = 12W / CV - Remote Const. Voltage 24VDC Driver					
			58 = 57.8"	15 CV = 15W / CV - Remote Const. Voltage 24VDC Driver					

¹ See page 2

23.4" 6W CV




DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim,
96W, 24VDC, 120-277VAC,
supplied in a Dry location
enclosure

OT96-JBX
Osram, Non-dim,
96W, 24VDC,
120-277VAC,
Wet location

46.3" 12W CV




DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim,
96W, 24VDC, 120-277VAC,
supplied in a Dry location
enclosure

OT96-JBX
Osram, Non-dim
24VDC, 120-277VAC,
Wet location

57.8" 15W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim,
96W, 24VDC, 120-277VAC,
supplied in a Dry location
enclosure

OT96-JBX
Osram, Non-dim
24VDC, 120-277VAC,
Wet location



Steel Bracket (incl.)



E83162 (L bracket)
Required when installing the
fixtures vertically on a wall