## Mini G-Cat

## inter-lux

## Photometry

Fitting	Polar diagram	LED	Supply	Power	Delivered output
	$\begin{array}{c} & 15 & 0 & 15 \\ & 30 & & 30 & & 45 \\ & 60 & & & & 60 \\ & 75 & & & & & 60 \\ & 75 & & & & & & 60 \\ & 75 & & & & & & & & & & \\ & 90 & & & & & & & & & & \\ & 75 & & & & & & & & & & & \\ & 90 & & & & & & & & & & & & \\ & 90 & & & & & & & & & & & & \\ & 90 & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & & & & \\ & 105 & & & & & & & & & & & & & & & & & & &$	90 CRI, 3000K	Constant Current 700mA	6W	389lm

**STOANE** LIGHTING

