



Surface
Recessed Trimmed
Recessed Trimless
Suspended

48V Track with Databus For Dali Or 0-10V



ST8-9500
Recessed Trimmed



ST3-9500
Recessed Trimless



ST6-9500
Suspended



ST1-9500
Surface



9518-S...
Adjustable Corner
Connector



9501-S-K...
End Feed




9503-S/B-M-E
Isolated Coupler



9503-S-K...
Straight Coupler




9511-K...
L Feed



STUCCHI MULTISYSTEM 48V

inter•lux

Recessed Trimmed 48V Track ST8 48V track with Databus



4' length


RAL 9005	9500-UL4/B-ST8-E
RAL 9016	9500-UL4/W2-ST8-E

8' length

RAL 9005	9500-UL8/B-ST8-E
RAL 9016	9500-UL8/W2-ST8-E

Mounting brackets required, 2 per 4' - S-9500/316

Recessed Trimless 48V Track ST3 48V track with Databus



4' length


RAL 9005	9500-UL4/B-ST3-E
RAL 9016	9500-UL4/W2-ST3-E

8' length

RAL 9005	9500-UL8/B-ST3-E
RAL 9016	9500-UL8/W2-ST3-E

Mounting brackets required, 4 per 4' - S-9500/315

Suspended 48V Track ST6 48V track with Databus



4' length


RAL 9005	9500-UL4/B-ST6-E
RAL 9016	9500-UL4/W2-ST6-E

8' length

RAL 9005	9500-UL8/B-ST6-E
RAL 9016	9500-UL8/W2-ST6-E

Suspension kits required, 2 per 4' - 9500-KIT1-1.5/3/5 (1.5m / 3m / 5m suspension)

Surface 48V Track ST1 48V track with Databus



4' length

RAL 9005	9500-UL4/B-ST1-E
RAL 9016	9500-UL4/W2-ST1-E

8' length




RAL 9005	9500-UL8/B-ST1-E
RAL 9016	9500-UL8/W2-ST1-E

CONNECTION HARDWARE


POLARISED 0-10V CONNECTION HARDWARE

Track power feeds and interconnectors have markings for V-, V+, D+ & D-, this polarity must be observed throughout the system.


For 0-10V installations the luminaires are polarity sensitive, you must ensure the data bus wiring does not create a ring structure and that polarity is maintained in relation to the polarity key on the track by using left handed / right handed, internal and external connectors. A failure-free 0-10V bus cannot be ensured if this is not in place. If the track installation requires the use of L T or X joints, it is possible to disconnect the data bus in these joints to avoid creating a ring. Pay attention at joints between track sections that the polarity key feature is on the same side across tracks. Miss-wiring will result in a short or sections on non-controllable lights.




Adjustable Corner Connector Compatible with all tracks




Isolated Coupler Compatible with all tracks




Left Handed End Feed Compatible with all tracks




Right Handed End Feed Compatible with all tracks




Internal L Feed Compatible with all tracks



External L Feed Compatible with all tracks



Straight Coupler Compatible with all tracks



MOUNTING AND MISC HARDWARE

RECESSED TRIMMED TRACK HARDWARE - ST8

Recessed multisystem track requires 2 mounting clamps [S-9500/316] per 4' of installed track.

Note: When installing Polarized track hardware ensure the connection hardware matches the track orientation and cable feed locations.

Recessed mounting clamp


Mounting clamp for ST8 Recessed trimmed track only



SILVER S-9500/316

End Cap (Recessed Trimmed)

For use with Recessed Trimmed track ONLY




RAL 9005 9504/ST8-B

RAL 9010 9504/ST8-W

Reinforced Bracket

Reinforced linear bracket for ST8 Recessed Trimmed track and ST6 Suspended track ONLY



SILVER 9500/323-SV


RECESSED TRIMLESS TRACK HARDWARE - ST3

Recessed multisystem track requires 4 mounting brackets [S-9500/315] per 4' of installed track.

Note: When installing Polarized track hardware ensure the connection hardware matches the track orientation and cable feed locations.

Reinforced Bracket


Reinforced linear bracket for ST3 Recessed Trimless track ONLY



RAL 9005 S-9500/314-B

End Cap (Recessed Trimless)

For use with Recessed Trimless track ONLY



RAL 9005 9504/ST3-B

RAL 9016 9504/ST3-W

Mounting Bracket

Mounting bracket for ST3 Recessed Trimless track, 4 required per 4'



SILVER S-9500/315

MOUNTING AND MISC HARDWARE


SUSPENDED TRACK HARDWARE - ST6

Suspended multisystem track requires 2 suspension kits [9500-KIT1.5] per cut length of track, or 3 per 8', whichever is greater. Note:

When installing Polarized track hardware ensure the connection hardware matches the track orientation and cable feed locations.

End Cap (Suspended)


For use with Recessed Suspended track ONLY



RAL 9005 9504/ST6-B
RAL 9010 9504/ST6-W

End Cap (Suspended) with wire feed hole


For use with Recessed Suspended track ONLY



RAL 9005 9504/ST6-B-F
RAL 9010 9504/ST6-W-F

Reinforced Bracket


Reinforced linear bracket for ST8 Recessed Trimmed track and ST6 Suspended track ONLY



SILVER 9500/323-SV

Suspension Kit


For use with ST6 Suspended Track ONLY



SILVER 9500-KIT1.5/3/5

Reinforced Corner

Reinforced corner bracket for ST6 Suspended track. Isolates tracks as standard, requires L feed to conduct power and data between tracks.




RAL 9005 S-9511/B-ST6
RAL 9010 S-9511/W-ST6

SURFACE TRACK HARDWARE - ST1

Note: When installing Polarised track hardware ensure the connection hardware matches the track orientation and cable feed locations.

End Cap (Surface)


For use with Surface track ONLY



RAL 9005 9504/ST1-B
RAL 9010 9504/ST1-W

End Cap (Surface) with wire feed hole

For use with Surface track ONLY



RAL 9005 9504/ST1-B-F
RAL 9010 9504/ST1-W-F