



Luminaire

- IP66 exterior-rated, miniature surface mounted fitting with a clean linear beam. Curved optic designed to discreetly light archways and window reveals.
- Surface mounted.
- Precision machined from 70 - 90% recycled aluminum.
- Linear beam (14.7° x 102.6°).
- 95+ CRI, multiple CCTs available.

Mounting

- SM = Surface Mounted

Power<sup>1</sup>

- 2 = 2W (Oscon Star, 181lm initial at 700mA, 2.9Vf)

CCT (95+ CRI)<sup>2</sup>

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Beam

- L = Linear (14.7° x 102.6°)

Finish

- CA = Clear Anodized
- CB = Classic Bronze 34
- W = Pure White, RAL9010
- BA = Black Anodized
- CF = Custom finish, specify RAL

Remote Driver<sup>3</sup>

- ECO30W-700 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures (wired in series per driver)
- SOLO50W-700 = 0-10V EldoLED SOLOdrive 50W for 1-16 fixtures (8 per output, wired in series)
- SOLO100W-700 = 0-10V EldoLED SOLOdrive 100W for 1-32 fixtures (8 per output, wired in series)

1. Wattage shown is for LED only, system wattage varies depending on driver selected.  
2. See photometric data sheet for delivered lumens.  
3. See driver information for details.

Ordering Information						
MS-ENIC	SM	2		L		
Model	Mounting	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Optic	Finish	+ Driver <sup>3</sup>
MS-ENIC	SM	2	927 930 935 940	L	CA CB W BL CF	ECO30W-700 SOLO50W-700 SOLO100W-700

