4" ProTools

WG-100SPTDL-SM

J-Box (by others)

Canopy

Mounting

Mounting

Screw (2)

Plate

Set

Screw

Fixture

Body

Installation Instructions

Downlight

Square Dark Cylinder
Surface Mount

IMPORTANT: Fixture(s) must be wired in series! Refer to driver wiring document

Luminaires must be installed by a qualified electrician. Check with local and national codes for proper installation.



To prevent electrical shock disconnect electrical supply before installation or servicing.

Never connect a live fixture!!!

Contractor is responsible for adequately reinforcing walls and/or ceilings to support fixture weight. Provide blocking when necessary.

Integral Driver

Step 1

Open the Box

Unpack luminaire unit.

Step 2

Ceiling Preparation

Mark location, cut opening, and mount J-Box. Pull power (and control) cable(s) inside.

Step 3

Electrical Connection

- From Fixture, feed cable through Mounting Plate, followed by Canopy.
- b Inside J-Box, connect power (and control) wire(s) using suitable connectors.


Step 4

Mount Luminaire

- Secure Canopy and Mounting Plate to J-Box using Mounting Screws.
- b Slip Fixture Body over Mounting Plate. Secure Luminaire with Set Screw. Energize!

Included in Box

- (1) Fixture Body with Integral Driver with connected cable
- (1) Mounting Plate
- (2) Mounting Screws
- (1) Canopy
- (1) Set Screw



Cross-Section of Fixture



