




20 Linear Direct/Indirect Suspended Ypsilon



Ypsilon shaped miniature suspended Direct, Indirect or Direct / Indirect Ypsilon for general, accent and decorative lighting.

Housing	Precision extruded aluminum for true dimensions and tolerances Standard and tailored lengths including corner configurations Finishes: white, black, silver and custom
Integration	Suspension from any surface
Distribution	Multiple lens options for diffuse, high efficiency and luminous effect
LED	Constant Voltage, 90+ CRI, 3 Steps MacAdam, 3W - 6W per foot L70 lifetime (TM21 Projected 85C) Static White (2700K-4000K) = 60,000 hours
Lens	OD - Opal Diffuser provides even, continuous line of light and general illumination SD - Satin Clear Diffuser provides high efficiency soft edge beam, general illumination MPL - Micro-prismatic lens provides lower brightness, general illumination
Driver	Remote driver Compatible with quality constant voltage drivers
Connectivity	Lutron Athena Wireless Node RF Casambi BlueTooth
Weight	0.5lbs per foot
Operating Temp	Suitable for operation in maximum ambient temperature of 35C (95F)
Warranty	5-year Limited (see complete company warranty information)
Certifications	ETL and ETL-C for dry and damp location, CE
Voltages	24V Fixture / 120-277VAC Driver (remote)



20 Linear Direct/Indirect Suspended Ypsilon

Model	Fixation	Length	Direct					Indirect					Finish	Options
			Lighting Pattern	Power ¹	CRI/CCT ²	Driver ³	Lens	Lighting Pattern	Power ¹	CRI/CCT ²	Driver ³	Lens		
WG-20LDI-Y	S48 (std) S96	41 x 36	D1 D2 D3 D4	L M	927 930 935 940	X S D010 DPH L3DAE L3DOE EL96 DALI	OD (std) MPL	D1 D2 D3 D4	L M	927 930 935 940	X S D010 DPH L3DAE L3DOE EL96 DALI	OD (std) SD	W (std) B S F	AWNRF BT 5C DC EM

- Model**
- WG-20LDI-Y = 20 Linear Direct/Indirect Suspended Ypsilon
- Fixation**
- S48 = 48" suspension cable standard, field-cuttable (standard)
 - S96 = 96" suspension cable, field-cuttable

- Length**
- 41 x 36 = 41" x 36" 9 sided Ypsilon

- Lighting Pattern**
- D1 = 3 x 24" Illuminated sections
 - D2 = 144" fully Illuminated
 - D3 = Non-Illuminated
 - D4 = Custom Illumination, specify sections

- Power¹**
- L = 3W/ft low power (24V)
D1, 18W
D2, 36W
 - M = 6W/ft mid power (24V)
D1, 36W
D2, 72W

- CRI/CCT (90+ CRI)²**
- 927 = 2700K
 - 930 = 3000K
 - 935 = 3500K
 - 940 = 4000K

- Driver (remote)³**
- X = No driver, ordered separately
 - S = Standard, non-dim driver 120-277V
 - D010 = eldoLED, 10%, 0-10V dimming, 120-277V
 - DPH = Phase Dimming, 1% dimming, 120V only
 - L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
 - L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
 - EL96 = eldoLED, 24V, 0.1% 0-10V Dimming
 - DALI = eldoLED DALI (DT6), 0.1% dimming (120-277V)

- Lens**
- OD = Satin opal diffuser (standard)
 - SD = Satin clear diffuser
 - MPL = Micro-prismatic lens


- Finish**
- W = White, 15% gloss, RAL 9010 (standard)
 - B = Black, 15% gloss, RAL 9005
 - S = Silver, 15% gloss, RAL 9006
 - F = Custom finished trim, specify RAL

- Options**
- AWNRF = Lutron Athena Wireless Node RF (specify with D010, EL96 or DALI)
 - BT = Wireless CAS - Casambi (specify with D010, EL96 or DALI)
 - 5C = 5" canopy (use with 4" Jbox)
 - DC = Dual circuit
 - EM = Emergency (remote)



D1 - 3 x 24" illuminated section



D2 - 144" fully illuminated



D3 - non-illuminated section



Whitegoods reserves the right to change any information without prior notice.

- Notes**
- Wattage is shown for LED boards only, system wattage varies depending on driver selected.
 - When specifying 20LDI please specify CRI / CCT and Driver for Direct and Indirect if different CRI / CCT / Driver is needed, i.e. 930-M-OD-D010-930-M-SD-D010. Refer to specsheet for delivered lumen data for all product configurations.
 - Remote power supply required. See power supply page for details.