

20 Linear Surface Frame Triangle




inter•lux








Contents

- 1 overview
- 2 specifications / configurator
- 3 photometry




Miniature surface mounted triangle for general, accent and decorative lighting.

- Surface mounted fixture with very shallow depth.
- Multiple lens options for diffuse, high efficiency and luminous effect.
- Extruded aluminum housing, easily installed. Field maintainable and upgradeable LED and driver without upsetting the ceiling.
- Efficacy up to 76 lumens per watt (delivered) @ 3000K, see photometry page for details.
- 90+ CRI, 3 Step MacAdam (Static White).
- L70 (TM21 Projected 85°C) Static White 60,000 hours.
- ETL and ETL-C for dry and damp locations.
- Lengths and angles factory-cut to exact field dimensions. Standard and custom corners.
- Powdercoat painted.



Screw clip
(SC)



T-bar grid clip
(GT9 / GT15)

20 Linear Surface Frame Triangle

Ordering Information										
WG-20LDL-FR		T								
Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish	Cable	Options
WG-20LDL-FR	SC GT9 ¹ GT15 ¹	T	24 x 24 x 24 36 x 36 x 36 48 x 48 x 48 A x A x A	L M	927 930 935 940	X S D010 DPH L3DAE L3DOE EL96 DALI	OD (std) MPL	W (std) B S F	C4 (std) C10 C20 C30	AWNRF BT EM

Model

- WG-20LDL-FR = 20 Linear Surface Frame Triangle

Fixation

- SC = Screw clip
- GT9 = 9/16" T-bar grid clip¹
- GT15 = 15/16" T-bar grid clip¹

Pattern

- T = 3-sided equilateral triangle

Length

- 24 x 24 x 24 = 24" x 24" x 24"
- 36 x 36 x 36 = 36" x 36" x 36"
- 48 x 48 x 48 = 48" x 48" x 48"
- A x A x A = specify inches to the nearest 0.25" (i.e. 72.25")

Power¹

- L = 3W/ft low power (24V)
 - 24 x 24 x 24, 18W
 - 36 x 36 x 36, 27W
 - 48 x 48 x 48, 36W
- M = 6W/ft mid power (24V)
 - 24 x 24 x 24, 36W
 - 36 x 36 x 36, 54W
 - 48 x 48 x 48, 72W

CRI / CCT (90+ CRI minimum)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Driver (remote)³

- X = No driver, ordered separately
- S = Standard, non-dim driver 120-277V
- D010 = eldoLED, 10%, 0-10V dimming, 120-277V
- DPH = Phase Dimming, 1% dimming, 120V only
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- EL96 = eldoLED, 24V, 0.1% 0-10V Dimming, 120-277V
- DALI = eldoLED DALI (DT6), 0.1% dimming (120-277V)

Lens

- OD = Satin opal diffuser (standard)
- MPL = Micro-prismatic lens

Finish

- W = White, 15% gloss, RAL 9010 (standard)
- B = Black, 15% gloss, RAL 9005
- S = Silver, 15% gloss, RAL 9006
- F = Custom finished trim, specify RAL

Cable

- C4 = 4' tray cable (plenum rated) (standard)
- C10 = 10' tray cable (plenum rated)
- C20 = 20' tray cable (plenum rated)
- C30 = 30' tray cable (plenum rated)

Options

- AWNRF = Lutron Athena Wireless Node RF (specify with D010, EL96 or DALI)
- BT = Wireless CAS - Casambi (specify with D010, EL96 or DALI)
- EM = Emergency LED driver (remote)

- Wattage shown is for LED boards only, system wattage varies depending on driver selected.
- See photometric data sheet for delivered lumens.
- Remote power supply required. See power supply page for details.

Lenses/Accessories



Opal Diffuser (OD)


Micro-prismatic Lens (MPL)

20 Linear Surface Frame Triangle

WG-20LDL-FR-T-X-24X24X24-...-OD-W¹

Delivered Lumens Per Foot

		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	1056	2112
	930	1152	2298
	935	1362	2730
	940	1620	3240



BEAM ANGLE (0-180) = 110.3

BEAM ANGLE (90-270) = 110.4

WG-20LDL-FR-T-X-36X36X36-...-OD-W

Delivered Lumens Per Foot

		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	1584	3168
	930	1728	3447
	935	2043	4095
	940	2430	4860

WG-20LDL-FR-T-X-48X48X48-...-OD-W

Delivered Lumens Per Foot


		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	2112	4224
	930	2304	4596
	935	2724	5460
	940	3240	6480

Power Multiplier				
	L [3 W/ft]		M [6 W/ft]	
9XX	0.5		1.0	
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot is applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

20 Linear Surface Frame Triangle

WG-20LDL-FR-T-X-24X24X24-...-MPL-W ¹			
Delivered Lumens Per Foot			
		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	1254	2508
	930	1362	2724
	935	1620	3240
	940	1926	3846



BEAM ANGLE (0-180) = 85.5
BEAM ANGLE (90-270) = 73.8

WG-20LDL-FR-T-X-36X36X36-...-MPL-W			
Delivered Lumens Per Foot			
		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	1881	3762
	930	2043	4086
	935	2430	4860
	940	2889	5769

WG-20LDL-FR-T-X-48X48X48-...-MPL-W			
Delivered Lumens Per Foot			
		Power	
		L [3 W/ft]	M [6 W/ft]
CCT	927	2508	5016
	930	2724	5448
	935	3240	6480
	940	3852	7692

Power Multiplier				
	L [3 W/ft]		M [6 W/ft]	
9XX	0.5		1.0	
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

1 Polar Plot is applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.