





Contents

- 1 overview
- 2 specifications / configurator
- 3 photometry




Continuous surface wall, ceiling or mullion mounted cove system that delivers an even wash of directed light to the ceiling above or the floor below, and redirected light to softly illuminate the wall behind the fixture.


- Continuous surface wall, ceiling or mullion mounted cove system that delivers an even wash of directed light to the ceiling above or the floor below, and redirected light to softly illuminate the wall behind the fixture.
- WedgeCove can be mounted as a Wall Mounted Uplight (WCWL), Wall Mounted Down Light or Ceiling Mounted Wall Wash (WCWLD).
- Light source positioned for optimum vertical spread of illumination.
- Extruded aluminum housing (powdercoat painted), easily installed internal LED tray assembly. Remote driver. Field replaceable LED boards.
- Micro-prismatic lens for high efficiency and soft edge beam without striations.
- Efficacy up to 110 lumens per watt (delivered) @ 3000K, see photometry page for details.
- 90+ CRI, 3 Step MacAdam.
- L70 (TM21 Projected 85C) Static White 50,000 hours.
- ETL and ETL-C for dry, damp or wet locations.





Wall Mounted Uplight
(WCWL)



Wall Mounted Down Light
(WCWLD)



Ceiling Mounted Wall Wash
(WCWLD)



Mounts to 4" J-box (by others)

Ordering Information

Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish	Options
WG-WCWL (up) WG-WCWLD (down light / wall wash)	SM	S	A A x B A x B x C A x B x A x B	XL L M	927 930 935 940	X S D010 DPH L3DAE L3DOE EL96 DALI	MPL	W (std) B S F	AWNRF BT MP EM

Model

- WG-WCWL = Wedge Cove Outdoor (up)
- WG-WCWLD = Wedge Cove Outdoor (down light / wall wash)

Fixation

- SM = Surface Mount to wall, ceiling or mullion

Pattern

- S = Straight run

Length

- 24 = 24"
- 36 = 36"
- 48 = 48"
- 60 = 60"
- XX = Specify inches to the nearest 0.25 (i.e. 72.25")
Max 1 piece 96" - nonstandard

Power¹

- XL = 1.5 W/ft extra low power (24V)
- L = 3.0 W/ft low power (24V)
- M = 6.5 W/ft mid power (24V)

CRI / CCT (90+ CRI minimum)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Driver (remote)³

- X = No driver, ordered separately
- S = Standard, non-dim driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- DPH = Phase Dimming, 1% dimming, 120V only
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- EL96 = Osram / EldoLED, 24V, 0.1% 0-10V Dimming, 120-277V
- DALI = eldoLED DALI (DT6), 0.1% dimming (120-277V)

Lens

- MPL = Micro-prismatic lens (standard)

Finish

- W = White, 15% gloss, RAL 9003 (standard)
- B = Black, 15% gloss, RAL 9005
- S = Silver, 15% gloss, RAL 9006
- F = Custom finish, specify RAL code

Options

- AWNRF = Lutron Athena Wireless Node RF
(specify with D010, EL96 or DALI)
- BT = Wireless CAS – Casambi
(specify with D010, EL96 or DALI)
- MP = Mounting plate for J-box
- EM = Emergency LED driver (remote)

¹ Wattage shown does not include power supplies/drivers.

² See photometric data sheet for delivered lumens.

³ See power supply page for details.

WedgeCove Outdoor

inter•lux

**WG-WCWL---MPL-W
DELIVERED LUMENS PER FOOT**


CCT	POWER		
	XL [1.5 W/ft]	L [3 W/ft]	M [6.5 W/ft]
927	185	364	779
930	204	400	857
935	204	400	857
940	213	417	893

Power Multiplier


	XL [1.5 W/ft]	L [3 W/ft]	M [6.5 W/ft]
	0.24	0.47	1.00

CCT Multiplier

	927	930	935	940
	0.91	1.00	1.00	1.04



**ISOILLUMINANCE - 48" MPL M 3500K
WG-WCWL---S-48-M-935---MPL-W***



*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.