



**General:** Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers.

Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.



14" (35W)  
20.3" (51W)  
40" (89W)

**Fixture Body:** Corrosion resistant 6060 Aluminum, Anodized (20 µm), Aluminum finish

**Trim:** Frameless, ideal for continuous runs. Extra clear glass - Tempered

**Mounting:** 316 Marine Grade Steel adjustable bracket.

**Dimensions/Weight:** 14" (6.39 lbs)

**Driver:** Integral 120-277V 1% (logarithmic curve) 0-10V dimming, or Non-Dim.

**Wattages:** 35W (14")

**Cable:** Fixture comes with 0.56' of cable (Power cable required, ordered separately).

**Safety features:** Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

**IP rating:** IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed. Available in Narrow Spot – Spot – Flood – Elliptic. Archiline PRO comes with Dark Light (Anti-glare) system as a standard feature.

**Color temperatures:** 2700K – 3000K – 3500K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at  $T_j$  65°C and  $T_a$  25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	14"	20.3"	40"
NSP	2441	3526	7052
SP	2526	–	7364
FL	2338	–	7174
EL	1831	–	5622


\*Values shown for 3000K

## Ordering Information


ARP	W	DL			ID			+ Cables <sup>1</sup>
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic	
ARP = Archiline PRO	W = Wall	DL = DarkLight	14 = 14"	35 = 35W	ID = Integral (0-10V dim)	27 = 2700K	NSP = Narrow Spot	E99826
			20 = 20.3"	51 = 51W		30 = 3000K	SP = Spot	E99822
			40 = 40"	89 = 89W		35 = 3500K	FL = Flood	E99823
						40 = 4000K	EL = Elliptic/Graze	E99824
								E99825

<sup>3</sup> See page 2


## 14" 35W ID



## 20.3" 51W ID



## 40" 89W ID



## Cables 0-10V

### E99826

39.4" power supply cable  
+0-10V dimming  
F 5 pin

### E99822

196.9" power supply cable  
+0-10V dimming  
F 5 pin

### E99823

39.4" extension cable for power  
+0-10V dimming  
M+F 5 pin

### E99824

196.9" extension cable for power  
+0-10V dimming  
M+F 5 pin

### E99825

393.7" extension cable for power  
+0-10V dimming  
M+F 5 pin