



**General:** Elin is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

**Fixture Body:** Brass (Chromium Plated).

**Diffuser:** Clear Glass.

**Trim:** Bezel.

**Mounting:** Semi-Recessed ceiling.

**Dimensions/Weight:** 0.8"@1W (0.11 lbs) - 0.8"@1.5W (0.15 lbs)

**Driver:** Remote. Constant Current 120-277V Dimmable 0-10V or Non-Dim.

**Operation:** Constant Current (CC).

**CC features:** Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

**CV features:** Possibility to use higher wattage drivers and feed multiple fixtures with less drivers; fixtures need to be wired in parallel.

**Wattages:** 1W (CC) – 1.5W (CC)

**Cable:** Fixture comes with 0.39' of power cable.

**IP rating:** IP20. Fixture is protected against solid objects greater than 0.04". Not suitable for Outdoor applications or any contact with water.

**ETL Certification:** ETL, dry location

**Optics:** Fixed, General distribution.

**Color temperatures:** 2700K – 3000K – 4000K – 5000K.

**CRI:** 90+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (1W CC)

0.8" (1.5W CC)

Delivered Lumens*	0.8" [1 CC]	0.8" [1.5 CC]
GE	107	143


\*Values shown for 3000K

Ordering Information							(Required)	
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	Housing <sup>2</sup>	Driver <sup>2</sup>
ELI = Elin	SFCH = Semi-Flush Chrome	D = Diamond Shaped Crystal	O8 = 0.8"	1 CC = 1W / Constant Current (350mA) 1.5 CC = 1.5W / Constant Current (500mA)	27 = 2700K <sup>1</sup> 30 = 3000K 40 = 4000K 50 = 5000K	GE = General distribution	<b>1W</b> E84916 E84335 <b>1.5W</b> E84917	ECO30W-XXX SOLO50W-XXX SOLO100W-XXX

<sup>1</sup> N/A for CV

<sup>2</sup> See page 2

**0.8" 1W CC**



**Housing**

**E84916**  
Recessed Housing



**E84335**  
Recessed Housing



**DRIVER OPTIONS (pick one)**


**C.C. Power supply options (remote only)**

**ECO30W-350**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-350**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtures

**SOLO100W-350**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtures

**0.8" 1.5W CC**



**Housing**

**E84917**  
Recessed Housing



**DRIVER OPTIONS (pick one)**

**C.C. Power supply options (remote only)**

**ECO30W-500**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-500**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtures

**SOLO100W-500**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtures