

# Envelope IP66 Surface Mount Rectangular



**General:** With a simple, elegant, and minimalist design, Envelope is a family of round or square wall mounted step lights suitable for most projects (available for both indoor and outdoor applications). A recessed asymmetric optic that guarantees full cut-off while providing outstanding performances and a multitude of sizes and colors complete the range.

**Fixture Body:** Powder Coated Aluminum.

**Diffuser:** Silicone resin.

**Mounting details:** Surface mounted. Mounts to a 2"x4" J-box (by others).

**Dimensions/Weight:** 4.7" x 3.5" (0.38 lbs)

**Driver:** Remote, Constant Voltage 24V DC, 120-277VAC Dimmable 0-10V or Non-Dim.

**Wattage/Size:** 1W (4.7" x 3.5")

**Cable:** Fixture comes with 0.98' of power cable.

**IP rating:** IP66 for protection against dust and water jets from any angle.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed, Asymmetric.

**Color temperatures:** 3000K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



4.7" x 3.5"(1W)


Delivered Lumens*		47 (1W)
AS		94

\*Values shown for 3000K

Ordering Information							
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	Driver (Required) <sup>1</sup>
EN66 = Envelope IP66	SRWH = Surface Mount, Rectangular White SRWG = Surface Mount, Rectangular Grey SRBG = Surface Mount, Rectangular Black Grey SRDB = Surface Mount, Rectangular Dark Brown	ME = Mono Emission	47 = 4.7" x 3.5"	1 CV = 1W / CV = Remote Constant Voltage 24V DC	30 = 3000K 40 = 4000K	AS = Asymmetric	OT96-D010 OT96-JBX



4.7" x 3.5" (1W)



## DRIVER OPTIONS (pick one)

### C.V. Power supply options (remote only)

#### OT96-D010

Osram, 10% 0-10V dim, 96W,  
24VDC, 120-277VAC, supplied  
in a Dry location enclosure

#### OT96-JBX

Osram, Non-Dim, 96W,  
24VDC, 120-277VAC,  
Wet Location