



Contents

- 2 product configurator
- 3 diagrams / drivers
- 4 photometry



16.1" (19W)



23.4" (38W)



35.8" (75W)

General: Skylum is a high-performance lighting system that focuses on having uniform distribution on the entire diffuser surface.

Skylum's clean look and multiple sizes make it the right fit for different applications, from retail to hospitality, office spaces and airports.

Fixture Body: Powder coated aluminum.

Diffuser: PMMA (Opal, or Micro-prismatic with UGR<19).

Mounting: Ceiling, surface mounted.

Dimensions/Weight: 16.1" (4.63 lbs) – 23.8" (8.38 lbs) – 35.8" (20.94 lbs).

Driver: Constant Current, Remote. 120-277V Dimmable 0-10V or Non-Dim.

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

Wattages: 19W (16.1") – 38W (23.8") – 75W (35.8").

Cable: Not included.

Safety features: Fixture is equipped with Electrostatic discharge protection and Surge Protection (2 KV).

IP rating: IP40. Fixture is protected against solid objects greater than 1 millimeter.

IK rating: X

ETL Certification: ETL, dry location

Optics: Opal or Micro-Prismatic diffuser.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 90.

Standard operating ambient temperature: -4°F / +122°F (-20°C/+50°C)

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	16.1" (19W)	23.4" (38W)	35.8" (75W)
OD	-	-	-
MPL	2270	4626	9193


*Values shown for 3000K

Ordering Information								(Required)
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp ¹	Optic	+	Driver
SKY = SKYLUM	RWH = Round White	SM = Surface Mount	16 = 16.1"	19 CC = 19W / Constant Current (600mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	OD = Opal Diffuser MPD = Micro-prismatic Diffuser		SOLO50W-600 SOLO100W-600

Ordering Information								(Required)
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp ¹	Optic	+	Driver
SKY = SKYLUM	RWH = Round White	SM = Surface Mount	24 = 23.8"	38 CC = 38W / Constant Current (1200mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	OD = Opal Diffuser MPD = Micro-prismatic Diffuser		SOLO50W-1200 SOLO100W-1200

Ordering Information								(Required)
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp ¹	Optic	+	Driver
SKY = SKYLUM	RWH = Round White	SM = Surface Mount	36 = 35.8"	75 CC = 75W / Constant Current (1000/1300mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	OD = Opal Diffuser MPD = Micro-prismatic Diffuser		SOLO100W-1000/1300

16.1" 19W 600mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)


SOLO50W-600

0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtures

SOLO100W-600

0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtures

23.8" 38W 1200mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)


SOLO50W-1200

0-10V EldoLED
SOLOdrive 50W
for 1 fixture

SOLO100W-1200

0-10V EldoLED
SOLOdrive 100W
for 1-2 fixtures

35.8" 75W 1000/1300mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

SOLO100W-1000/1300

0-10V EldoLED
SOLOdrive 100W
for 1 fixture