

Contents

- 2 Buzzer Pro Path product configurator diagrams / drivers
- 3 Buzzer Pro Path + Wall product configurator diagrams / drivers

General: Buzzer Pro is part of a comprehensive family of bollards, path markers and wall fixtures designed for the most various applications, from pedestrian walkways to public parks, commercial buildings and residential areas.

With no up-light component (Dark skies compliant), two distributions (180° and 360°) and multiple sizes available, Buzzer Pro can easily fit into every design.

Buzzer Pro's special optic design provides no shadows at the bottom of the fixture, making the ground evenly illuminated.

Fixture Body: Open pore Anodized and Powder Coated Die-Cast Aluminum (5.4"x3.1" & 5.1"x3.0"). Galvanized Iron, Marine Grade (4.7"x5.7").

Diffuser: UV Resistant Polycarbonate.

Mounting: Standard Mounting Base (Provided with fixture). Ground peg available upon request. Anchor bolts available upon request for 4.7"x5.7" version ONLY.

Dimensions/Weight: Path: 4.7"x5.7" (1.9 lbs)

Path + Wall (ADA compliant for Wall installation 27"+ AFF): 5.4"x3.1" (2 lbs) – 5.1"x3.0" (2 lbs).

Driver: Remote, 120-277V Dimmable 0-10V.

Wattages: 6.5W (5.4"x3.1" & 5.1"x3.0") – 7.2W (4.7"x5.7").

Cable: Fixture comes with 6' of power cable.

Safety features: Fixture is equipped with Electrostatic discharge protection and Surge Protection (1 KV).

IP rating: IP65 for protection against dust and moderate water jets from any angle.

IK rating: IK 09 (5.4"x3.1" & 5.1"x3.0"), IK 10 (4.7"x5.7")

ETL Certification: ETL, wet location

Optics: Fixed, with asymmetric (180°) or round (360°) Light Emission.

Color temperatures: 2200K – 2700K – 3000K – 4000K.

CRI: 80+

BUG Rating: B0-U0-G0 (4.7"x5.7" version)

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Path



Ø4.7" x 5.7"H 6.5W

Path + Wall



Ø5.4" x 3.1"H 6.5W RE in BG



Ø5.4" x 3.0"H 6.5W RE in DB



Ø5.1" x 3.0"H 6.5W AE in GR



Ø5.1" x 3.0"H 6.5W AE in GN


Delivered Lumens*	Ø5" [6.5 - CC]	Ø5" [7.2W - CC]
RE	262	211
AE	111	82

*Values shown for 3000K

BUZZER PRO PATH

Mounting Accessories									
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required)	Mounting Accessories (optional)
BZP = Buzzer Pro	RBOBG = Round Bollard, Black Grey RBOGR = Round Bollard, Grey RBODB = Round Bollard, Dark Brown	RE = Round Emission AE = Asymmetric Emission	5x6 = Ø4.7" X 5.7"H	7 CC = 6.5W / Remote Driver (350 mA)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	GE = General Emission		ECO30W-350 SOLO50W-350 SOLO100W-350	W-F500001 (anchor bolts) 14931 (ground peg)

Ø4.7" x 5.7"H 6.5W 350mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W
for 1-2 fixtures


SOLO50W-350

0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures


SOLO100W-350

0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures

Mounting Accessories



W-F500001
(anchor bolts)




14931
(ground peg)

BUZZER PRO PATH + WALL

Mounting Accessories									
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required)	Mounting Accessories (optional)
BZP = Buzzer Pro	RBOBG = Round Bollard, Black Grey RBOGR = Round Bollard, Grey RBODB = Round Bollard, Dark Brown RBOGN = Round Bollard, Green	RE = Round Emission AE = Asymmetric Emission	5x3 = Ø5.4" X 3.1"H 5x3 = Ø5.1" X 3.0"H	7 CC = 7.2W / Remote Driver (200 mA)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	GE = General Emission		ECO30W-200 SOLO50W-200 SOLO100W-200	14931 (ground peg)

Ø5.4" x 3.1"H 7.2W 200mA




DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-200	SOLO50W-200	SOLO100W-200
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Ø5.1" x 3.0"H 7.2W 200mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-200	SOLO50W-200	SOLO100W-200
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Mounting Accessories

