

## Contents

- 2 Single Emission product configurator diagrams / drivers
- 3 Quad Emission product configurator diagrams / drivers

**General:** Buzzer\_Q is part of a comprehensive family of bollards and path markers designed for the most various applications, from pedestrian walkaways to public parks, commercial buildings and residential areas.

With no up-light component (Dark skies compliant), two distributions (180° and 360°) and multiple sizes available, Buzzer\_Q can easily fit into every design.

Buzzer\_Q's special optic design provides no shadows at the bottom of the fixture, making the ground evenly illuminated.

**Fixture Body:** Marine Grade. Open pore Anodized and Powder Coated Die-Cast Aluminum.

**Diffuser:** UV Resistant Polycarbonate.

**Mounting:** Standard Mounting Base (Provided with fixture). Ground peg available upon request.

**Dimensions/Weight:** 15.8" (4.41 lbs) – 27.6" (6.17 lbs) – 41.3" (7.72 lbs).

**Driver:** Remote, 120-277V Dimmable 0-10V.

**Wattages:** 5.5W (Single Emission) – 11.5W (Quad Emission).

**Cable:** Fixture comes with 4.17' of power cable.

**Safety features:** Fixture is equipped with Electrostatic discharge protection and Surge Protection (0.5 KV).

**IP rating:** IP65 for protection against dust and moderate water jets from any angle.

**IK rating:** IK 09

**ETL Certification:** ETL, wet location

**Optics:** Fixed, with Single (180°) or Quad (360°) Light Emission.


**Color temperatures:** 2200K – 2700K – 3000K – 4000K.

**CRI:** 80+


**BUG Rating:** B1-U0-G0 (Dark Sky Compliant)

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.


**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



6.5" x 3" x 15.8"H  
(SE 5.5W / QE 11.5W)



6.5" x 3" x 27.6"H  
(SE 5.5W / QE 11.5W)



6.5" x 3" x 41.3"H  
(SE 5.5W / QE 11.5W)


Delivered Lumens*	[6 - CC]	[12 - CC]
SE	525	–
QE	–	871

\*Values shown for 3000K

## SINGLE EMISSION

Mounting Accessories									
BZQ		SE		6 - CC		GE			
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required)	Mounting Accessories (optional)
BZQ = Buzzer Q	RBOBG = Rectangular Bollard, Black Grey RBOGR = Rectangular Bollard, Grey RBODB = Rectangular Bollard, Dark Brown	SE = Single Emission	16 = 6.5" X 3" X 15.8"H 28 = 6.5" X 3" X 27.6"H 41 = 6.5" X 3" X 41.3"H	6 CC = 5.5W / Constant Current (350mA)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	GE = General Emission		ECO30W-350 SOLO50W-350 SOLO100W-350	W-F900004 (anchor bolts)

### 6.5" x 3" x 15.8"H 5.5W 350mA




#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

### 6.5" x 3" x 27.6"H 5.5W 350mA




#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

### 6.5" x 3" x 41.3"H 5.5W 350mA



#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

## Mounting Accessories




W-F900004  
(ground peg)

## QUAD EMISSION

Mounting Accessories									
BZQ		QE		12 - CC		GE			
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required)	Mounting Accessories (optional)
BZQ = Buzzer Q	RBOBG = Rectangular Bollard, Black Grey RBOGR = Rectangular Bollard, Grey RBODB = Rectangular Bollard, Dark Brown	QE = Quad Emission	16 = 6.5" X 3" X 15.8"H 28 = 6.5" X 3" X 27.6"H 41 = 6.5" X 3" X 41.3"H	12 CC = 11.5W / Constant Current (700mA)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	GE = General Emission		ECO30W-700 SOLO50W-700 SOLO100W-700	W-F900004 (anchor bolts)

### 6.5" x 3" x 15.8"H 11.5W 700mA




#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

### 6.5" x 3" x 27.6"H 11.5W 700mA




#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

### 6.5" x 3" x 41.3"H 11.5W 700mA



#### DRIVER OPTIONS (pick one)

##### C.C. Power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

## Mounting Accessories



W-F900004  
(ground peg)