




FLEX 6x12 HORIZONTAL

0.24x0.47"

- STATIC WHITE
- FREE CUT
- TUNABLE WHITE
- WARM DIM



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67, IP20
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
WARRANTY	5 Years

DRIVERS STATIC WHITE (CRI >90 Ra)

SPECIFICATION (MINIMUM BEND DIAMETER >2.4" / 60 mm)

- DRIVER OPTIONS (See driver page for details)
- IES FILES

D010 = eldoLED, 10%, 0-10V dimming, 120-277V	DALI-DT6 = eldoLED DALI (DT6), 0.1% dimming, 120-277V
EL96 = eldoLED 24V, 0.1% 0-10V dimming, 120-277V	UNV96-WL = 0-10V / Phase Dim 96W Wet Location, 1% dimming, 120-277V
DPH = Phase Dimming, 1% dimming, 120V only	
L3D0E = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V	UNV384-WL = 0-10V / Phase Dim 384W Wet Location, 1% dimming, 120-277V

Cut Interval	DELIVERED LUMENS lm/ft							
	1800K	2400K	2700K	3000K	3500K	4000K	6000K	
S05 50 mm (2")	30	39	43	46	47	49	48	
S10 50 mm (2")	58	76	82	89	90	93	92	
L05 50 mm (2")	30	39	43	46	47	49	48	
L10 50 mm (2")	58	76	82	89	90	93	92	

- ACCESSORIES

ORDERING INFORMATION								
MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH	DRIVERS
63S0612H Flex 6x12 Horizontal	1 White	C18 1800K	S05 5 W/m (10m max.)	E End	7 IP67	003 0.3m (1ft)	.XXXX Length in inches	D010 EL96 DPH L3D0E DALI-DT6 UNV96-WL UNV384-WL
		C24 2400K	1.5 W/ft (32.8ft max.)	B Bottom		010 1m (3.3ft)		
		C27 2700K	S10 10 W/m (5m max.)	SL Side Left	030 3m (9.8ft)			
		C30 3000K	3 W/ft (16.4ft max.)	SR Side Right	050 5m (16.4ft)			
		C35 3500K	L05 5 W/m (16m max.)		100 10m (32.8ft)			
		C40 4000K	1.5 W/ft (52.5ft max.)					
		C60 6000K	L10 10 W/m (8m max.) 3 W/ft (26.2ft max.)					
63S0612H	1							

STATIC WHITE - HIGH OUTPUT (CRI >90 Ra)

SPECIFICATION (MINIMUM BEND DIAMETER >2.4" / 60 mm)

- DRIVER OPTIONS (See driver page for details)
- IES FILES

D010 = eldoLED, 10%, 0-10V dimming, 120-277V	DALI-DT6 = eldoLED DALI (DT6), 0.1% dimming, 120-277V
EL96 = eldoLED 24V, 0.1% 0-10V dimming, 120-277V	UNV96-WL = 0-10V / Phase Dim 96W Wet Location, 1% dimming, 120-277V
DPH = Phase Dimming, 1% dimming, 120V only	
L3D0E = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V	UNV384-WL = 0-10V / Phase Dim 384W Wet Location, 1% dimming, 120-277V

Cut Interval	DELIVERED LUMENS lm/ft							
	1800K	2400K	2700K	3000K	3500K	4000K	6000K	
S10 62.5 mm (2.5")	88	115	125	135	138	138	140	




ORDERING INFORMATION								
MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH	DRIVERS
63S0612HOH Flex 6x12 Horizontal High Output	1 White	C18 1800K	S10 10 W/m (7m max.)	E End	7 IP67	003 0.3m (1ft)	.XXXX Length in inches	D010 EL96 DPH L3D0E DALI-DT6 UNV96-WL UNV384-WL
		C24 2400K	3 W/ft (23ft max.)	B Bottom		010 1m (3.3ft)		
		C27 2700K		SL Side Left	030 3m (9.8ft)			
		C30 3000K		SR Side Right	050 5m (16.4ft)			
		C35 3500K			100 10m (32.8ft)			
		C40 4000K						
		C60 6000K						
63S0612HOH	1		S10					

FLEX 6x12 HORIZONTAL

0.24x0.47"



- STATIC WHITE
- FREE CUT
- TUNABLE WHITE
- WARM DIM



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67, IP20
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
WARRANTY	5 Years

DRIVERS **STATIC WHITE FREE CUT (CRI >90 Ra)**
 SPECIFICATION (MINIMUM BEND DIAMETER >2.4" / 60 mm)

- IES FILES

DRIVER OPTIONS (See driver page for details)	
D010 = eldoLED, 10%, 0-10V dimming, 120-277V	DALI-DT6 = eldoLED DALI (DT6), 0.1% dimming, 120-277V
EL96 = eldoLED 24V, 0.1% 0-10V dimming, 120-277V	UNV96-WL = 0-10V / Phase Dim 96W Wet Location, 1% dimming, 120-277V
DPH = Phase Dimming, 1% dimming, 120V only	
L3D0E = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V	UNV384-WL = 0-10V / Phase Dim 384W Wet Location, 1% dimming, 120-277V

Cut Interval	DELIVERED LUMENS lm/ft							
	1800K	2400K	2700K	3000K	3500K	4000K	6000K	
SF05 Free Cut	30	39	43	46	47	49	48	
SF10 Free Cut	58	76	82	89	90	93	92	

- ACCESSORIES



ORDERING INFORMATION								
MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH	DRIVERS
63S0612H Flex 6x12 Horizontal	1 White	C18 1800K	SF05 5 W/m (11m max.) 1.5 W/ft (36.1ft max.)	E End B Bottom SL Side Left SR Side Right	7 IP67 2 IP20	003 0.3m (1ft)	.XXXX Length in inches	D010 EL96 DPH L3D0E DALI-DT6 UNV96-WL UNV384-WL
		C24 2400K				010 1m (3.3ft)		
		C27 2700K	030 3m (9.8ft)					
		C30 3000K	050 5m (16.4ft)					
		C35 3500K	100 10m (32.8ft)					
		C40 4000K						
C60 6000K								
63S0612H	1							




FLEX 6x12 HORIZONTAL

0.24x0.47"

- STATIC WHITE
- FREE CUT
- TUNABLE WHITE
- WARM DIM



Horizontal Bending



SPECIFICATION

MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67, IP20
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
WARRANTY	5 Years

DRIVERS

TUNABLE WHITE (CRI >90 Ra)

SPECIFICATION (MINIMUM BEND DIAMETER >3.9" / 100 mm)

DRIVER OPTIONS (See driver page for details)

DALI-DT6 = eldoLED DALI (DT6), 0.1% dimming, 120-277V
DALI-DT8 = eldoLED DALI (DT8), 0.1% dimming, 120-277V

	Cut Interval	DELIVERED LUMENS lm/ft						
		1800K	2400K	2700K	3000K	3500K	4000K	6000K
CT08	50 mm (2")	32	45	50	52	52	53	51

ACCESSORIES




ORDERING INFORMATION

MODEL	JACKET	CCT (LOW)	CCT (HIGH)	LED TYPE*	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH	DRIVERS
63S0612H Flex 6x12 Horizontal	1 White	C18 1800K	24 2400K	CT08 2x8 W/m (5m max.) 2x2.4 W/ft (16.4ft max.) <small>* Rated wattage is maximum wattage per channel. Combined power must also not exceed this value.</small>	E End	7 IP67	003 0.3m (1ft)	.XXXX Length in inches	DALI-DT6 DALI-DT8
		C24 2400K	27 2700K		B Bottom	2 IP20	010 1m (3.3ft)		
		C27 2700K	30 3000K		SL Side Left		030 3m (9.8ft)		
		C30 3000K	35 3500K		SR Side Right		050 5m (16.4ft)		
		C35 3500K	40 4000K				100 10m (32.8ft)		
		C40 4000K	60 6000K						
63S0612H	1			CT08					

FLEX 6x12 HORIZONTAL

0.24x0.47"

- STATIC WHITE
- FREE CUT
- TUNABLE WHITE
- WARM DIM



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67, IP20
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
WARRANTY	5 Years

DRIVERS **WARM DIM (CRI >90 Ra)**
 SPECIFICATION (MINIMUM BEND DIAMETER >3.9" / 100 mm)

IES FILES

DRIVER OPTIONS (See driver page for details)
 MAGSDM96-WD = 0-10V / Phase Dim 96W, 0.1% CCR Dimming for Warm Dim, 120-277V (Phase - 120V only)

	Cut Interval	DELIVERED LUMENS lm/ft	
		2700K	3000K
12R	50 mm (2")	70	76

ACCESSORIES

ORDERING INFORMATION										
MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH	DRIVERS		
63S0612H Flex 6x12 Horizontal	1 White	C2718W 2700-1800K C3018W 3000-1800K	12R 12 W/m (5m max.) 3.7 W/ft (16.4ft max.)	E End B Bottom SL Side Left SR Side Right	7 IP67 2 IP20	003 0.3m (1ft)	.XXXX Length in inches	MAGSDM96-WD		
						010 1m (3.3ft)				
						030 3m (9.8ft)				
						050 5m (16.4ft)				
						100 10m (32.8ft)				
63S0612H	1		12R					MAGSDM96-WD		

FLEX 6x12 HORIZONTAL


0.24x0.47"

ACCESSORIES


- STATIC WHITE
- FREE CUT
- TUNABLE WHITE
- WARM DIM

TYPE Aluminium profile
MOUNTING Surface mount

ORDERING INFORMATION		
MODEL	FINISH	LENGTH
63S0612H	5AP Silver	0020 20mm (0.79")
	2AP Black	1000 1000mm (39.37")
63S0612H		



- DRIVERS
- IES FILES



- ACCESSORIES

TYPE Stainless Mounting Clip
MOUNTING Surface mount

ORDERING INFORMATION		
MODEL	FINISH	LENGTH
63S0612H	5SC Silver	0020 20mm (0.79")
	2SC Black	
63S0612H		0020



TYPE Stainless Bendable Profile
MOUNTING Surface mount

ORDERING INFORMATION		
MODEL	FINISH	LENGTH
63S0612H	5SC Silver	1000 1000mm (39.37")
	2SC Black	
63S0612H		1000