



Contents	
2	product configurator
2	diagrams / drivers



20.8" (8.5W)
46" (22.6W)

General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

- Fixture Body:** Corrosion resistant 6060 Aluminum, Anodized (20 µm).
- Trim:** Aluminum Frame or Frameless. Extra clear glass – Tempered. Individual fixture end caps can be removed and are required only at the ends of each run, guaranteeing continuous illumination.
- Mounting/Casing:** Corrosion resistant 6060 Anodized Aluminum casing (required for Recessed in-ground installations) or Aluminum Springs (required for Recessed Wall/Ceiling applications).
- Drive-over:** Up to 4,409 lbs.
- Dimensions/Weight:** 20.8" (1.48 lbs) – 46" (2.95 lbs).
- Driver:** Integral 120VAC w/DMX interface.
- Wattages (Remote/Integral):** 8.5W (20.8") – 22.6W (46")
- Cable:** Fixture comes with 0.82' of cable (Power cable required, ordered separately).
- Safety features:** Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP68 for temporary submersion up to 10' depth for up to a maximum of 1 hr.

IK rating: IK 08

ETL Certification: ETL, wet location

Optics: Fixed. Available in Elliptic Graze.

Color temperatures: RGBW with 3000K Warm White or RGBW with 4000K Neutral White.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Nominal Lumens*	20.8"	46"
Red	117	312
Green	204	544
Blue	69	184
White 3K/4K	303/321	808/856

*Values shown for 3000K




Ordering Information


Product	Mounting/ Frame	Type	Length	Wattage/Operation	Color Temp	Optic	+	Housing (Required)	Cables (Required)	Accessories
XEP = Xenia Pro	RF = Recessed Frameless RAF = Recessed Aluminum Frame	F = Fixed	21 = 20.8" ¹	9 IDMX = 8.5W / Integral 120VAC w/DMX interface	R3 = RGBW 3K R4 = RGBW 4K	ELSP = Elliptical Spot (13°x39°)		99918 (21) 99919 (46)	IDMX Power: E83043 E89189 E83044 E89186 E83045 E98994 E83046 E98493 E83047 E98494 E98993 E89187 89365	(end caps) 99917 (RF) 83188 (RAF) (instl. spring) 99818 (RAF) (fixing bracket) 98949 (RF) C-F400006 (RF)
			46 = 46"	23 IDMX = 22.6W / Integral 120VAC w/DMX interface						

¹ 20.8" available in 120/277V upon request.


20.8" 8.5W IDMX




HOUSING 99918



46" 22.6W IDMX



HOUSING 99919



IDMX Power Cables

E83043	E83044	E83045	E83046	E83047
59" line volt. power feed cable F 4 pin M12	196" line volt. power feed cable F 4 pin M12	39" line volt. power extension cable M+F 4 pin M12	196.9" line volt. power extension cable M+F 4 pin M12	393.7" line volt. power extension cable M+F 4 pin M12

DMX data Cables:

E89189	E89186	E98494	E98493	E98994
196.9" DMX cable M 5 pin M12 to bare leads	196.9" DMX cable M 5 pin M12 + M 3 pin XLR	196.9" DMX cable M 5 pin M12 + F 3 pin XLR	196.9" DMX cable M 5 pin M12 + M 5 pin XLR	39.4" DMX extension M+F 5 pin M12
E98993	E89187	89365		
196.9" DMX extension M+F 5 pin M12	393.7" DMX extension M+F 5 pin M12	DMX Terminator		

Accessories

83188	99917	99818
End caps (pair) One pair required per in-grade run for RAF	Ceiling or wall recessed installation spring for RF	Ceiling or wall recessed installation spring for RAF



98949

1.8"-2.6" Adjustable
Fixing bracket for
surface mount
applications for RF



C-F400006

Fixing bracket for RF

