



Contents	
2	product configurator
2	diagrams / drivers
3	photometry



General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

- 14.4" (9W)
- 24.8" (17W)
- 36.6" (26.2W)
- 48.4" (35.4W)
- 60.2" (44W)

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).
Trim: Frameless, ideal for continuous runs.
Mounting: Adjustable steel brackets, available in different lengths.
Dimensions/Weight: 14.4" (1.21 lbs) – 24.8" (1.76 lbs) – 36.6" (2.43 lbs) – 48.4" (3.09 lbs) – 60.2" (3.75 lbs)
Driver: Integral, 120/277VAC Non-Dim or 0-10V Dim down to 10% (Dimming N/A for 14.1").
Wattages: 9W (14.4") – 17W (24.8") – 26.2W (36.6") – 35W (48.4") – 44W (60.2")
Cable: IND fixtures provided with a pair of 9.8" Power in-and-out cables. ID fixtures provided with a pair of 9.8" Power in-and-out cables plus a pair of 9.8" Dimming in-and-out cables. (Power and Dimming cables required, ordered separately).
Safety features: Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.
IP rating: IP66. Fixture is protected against dust and direct exposure to powerful water jets.
IK rating: IK 10
ETL Certification: ETL, wet location


Optics: Fixed. Available in Narrow Flood – Elliptic Narrow Flood – Elliptic Flood – Wall Washer. Anti-glare visors available as accessory.
Color temperatures: 2700K – 3000K – 3500K – 4000K.
CRI: 80+
Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	14.4"	24.8"	36.6"	48.4"	60.2"
NFL	812	1623	2259	3012	3765
ELNFL	914	1827	2542	3390	4237
ELFL	720	1439	2002	2670	3338
WW	925	1850	2574	3432	4290


*Values shown for 3000K

Ordering Information										
XEP	W	OB								
Product	Mounting/ Frame	Type	Length	Wattage/Operation	Color Temp	Optic	+	Cables ¹	Fixing Brackets ¹	Anti-glaring ¹
XEP = Xenia PRO	W = Wall	OB = Open Beam	14 = 14.4"	9 IND = 9W / Integral (120/277VAC Non Dim)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NFL = Narrow Flood (29°) ELNFL = Elliptic Narrow Flood (29°x 92°) ELFL = Elliptic Flood (35°x 47°) WW = Wall Washer (85°)		E83043	E98949 (RF)	E98782 (14)
			25 = 24.8"	17 IND = 17W / Int. Non-dim 17 ID = 17W / Int. 0-10V dim				E83044	E89045	E98783 (25)
			37 = 36.6"	26 IND = 26.2W / Int. Non-dim 26 ID = 26.2W / Int. 0-10V dim				E83045	E89046	E98784 (37)
			48 = 48.4"	35 IND = 35.4W / Int. Non-dim 35 ID = 35.4W / Int. 0-10V dim				E83046	E89047	E98785 (48)
			60 = 60.2"	44 IND = 44W / Int. Non-dim 44 ID = 44W / Int. 0-10V dim				E83047	C-F400006 (RF)	E99778 (60)
								ID Only: E99216	C-F400008	
								E89190		
								E98437		
								E98149		
								E89188		


14.4" 9W IND




24.84" 17W IND




36.6" 26.2W ID



44.8" 35.4W ID



60.2" 44W ID



Cables

E83043	E83044	E83045	E83046	E83047
59" line volt. power feed cable F 3 pin M12	196" line volt. power feed cable F 3 pin M12	39" line volt. power extension cable M+F 3 pin M12	196" line volt. power extension cable M+F 3 pin M12	393" line volt. power extension cable M+F 3 pin M12
E99216 ²	E89190 ²	E98437 ³	E98149 ³	E89188 ³
59.1" DC(+) power cable F 4 pin M12	196.9" DC(+) power cable F 4 pin M12	39" extension power cable M+F 4 pin M12	196.9" extension power cable M+F 4 pin M12	393.7" extension power cable M+F 4 pin M12

² One Female DC(+) and Male DC(-) required per driver

³ Required between fixtures powered from the same driver

Accessories

Steel fixing brackets		Anti-glaring accessory	
1.8-2.6"	E98949	14.4"	E98782
3.5"	E89045	24.8"	E98783
5.9"	E89046	36.6"	E98784
11.8"	E89047	48.4"	E98785
		60.2"	E99778

