



| Contents |                      |
|----------|----------------------|
| 2        | product configurator |
| 2        | diagrams / drivers   |



19.7" (8.5W)  
46.5" (22.6W)

**General:** Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

**Fixture Body:** Corrosion resistant 6060 Aluminum, Anodized (20 µm).

**Trim:** Frameless, ideal for continuous runs.

**Mounting:** Adjustable steel brackets available in different lengths.

**Dimensions/Weight:** 21.1" (1.54 lbs) – 46.5" (2.87 lbs)

**Driver:** Integral, 120VAC with DMX interface.

**Wattages:** 8.5W (19.7") – 22.6W (46.5")

**Cable:** Fixture comes with 0.98' of cable (Power cable required, ordered separately).

**Safety features:** Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.

**IP rating:** IP66. Fixture is protected against dust and direct exposure to powerful water jets.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Open Beam. Available in Elliptic Graze. Anti-glare visors available as accessory.

**Color temperatures:** RGBW with 3000K Warm White or RGBW with 4000K Neutral White.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.


| Nominal Lumens* | 19.7"   | 46.5"   |
|-----------------|---------|---------|
| Red             | 117     | 312     |
| Green           | 204     | 544     |
| Blue            | 69      | 184     |
| White 3K/4K     | 303/321 | 808/856 |

\*Values shown for 3000K


| Ordering Information |                |                |                         |                                                   |                              |                                           |   |                                                                                |                                                                      |                                                                             |
|----------------------|----------------|----------------|-------------------------|---------------------------------------------------|------------------------------|-------------------------------------------|---|--------------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------------------------------------------------------------------|
| Product              | Mounting/Frame | Type           | Length                  | Wattage/Operation                                 | Color Temp                   | Optic                                     | + | Cables                                                                         | Fixing Brackets                                                      | Accessories                                                                 |
| XEP = Xenia Pro      | W = Wall       | OB = Open Beam | 20 = 19.7" <sup>1</sup> | 9 IDMX = 8.5W / Integral 120VAC w/DMX interface   | R3 = RGBW 3K<br>R4 = RGBW 4K | ELNFL = Elliptical Narrow Flood (26°x43°) |   | E83043<br>E83044<br>E83045<br>E83046<br>E83047                                 | 98949 (RF)<br>89045<br>89046<br>89047<br>C-F400006 (RF)<br>C-F400008 | (Anti-glaring)<br>98951 (20)<br>98952 (47)<br><br>(DMX Terminator)<br>89365 |
|                      |                |                | 47 = 46.5"              | 23 IDMX = 22.6W / Integral 120VAC w/DMX interface |                              |                                           |   | ID Only:<br>E89189<br>E89186<br>E98494<br>E98493<br>E98994<br>E98993<br>E89187 |                                                                      |                                                                             |

<sup>1</sup> 19.7" available in 120/277V upon request.

## 19.7" 8.5W IDMX



## 46.5" 22.6W IDMX



## Cables

|                                                                   |                                                                   |                                                                        |                                                                         |                                                                         |                                                        |
|-------------------------------------------------------------------|-------------------------------------------------------------------|------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------|
| <b>E83043</b><br>59" line volt. power feed cable<br>F 3 pin M12   | <b>E83044</b><br>196" line volt. power feed cable<br>F 3 pin M12  | <b>E83045</b><br>39" line volt. power extension cable<br>M+F 3 pin M12 | <b>E83046</b><br>196" line volt. power extension cable<br>M+F 3 pin M12 | <b>E83047</b><br>393" line volt. power extension cable<br>M+F 3 pin M12 | <b>E89189</b><br>196.9" DMX cable<br>M 5 pin M12       |
| <b>E89186</b><br>196.9" DMX cable<br>M 5 pin M12 +<br>M 3 pin XLR | <b>E98494</b><br>196.9" DMX cable<br>M 5 pin M12 +<br>F 3 pin XLR | <b>E98493</b><br>196.9" DMX cable<br>M 5 pin M12 +<br>M 5 pin XLR      | <b>E98994</b><br>196.9" DMX cable<br>M 5 pin M12 +<br>M 5 pin XLR       | <b>E98993</b><br>196.9" DMX extension M+F<br>5 pin M12                  | <b>E89187</b><br>393.7" DMX extension M+F<br>5 pin M12 |

## Accessories

| Steel fixing brackets |             | Anti-glaring accessory |       |
|-----------------------|-------------|------------------------|-------|
| 1.8-2.6"              | E98949 (RF) | 20"                    | 98951 |
| 3.5"                  | E89045      | 46.5"                  | 98952 |
| 5.9"                  | E89046      |                        |       |
| 11.8"                 | E89047      |                        |       |



C-F400006 (RF)

C-F400008 (2X)

