



General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).

Trim: Aluminum Frame or Frameless. Extra clear glass – Tempered.

Mounting/Housing: Corrosion resistant 6060 Anodized Aluminum Housing (required for Recessed in-ground installations) or Aluminum Springs (required for Recessed Wall/Ceiling applications).

Drive-over: Up to 4,409 lbs.

Dimensions/Weight: 8.1" (0.9 lbs)

Driver: Remote DMX Constant current 350mA driver.

Wattages: 8W (8.1")

Cable: Fixture comes with 39.4" long cable with bare leads at the end.

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP68 for temporary submersion up to 10' depth for up to a maximum of 1 hr.

IK rating: IK 08

ETL Certification: ETL, wet location

Optics: Fixed, Radial (Blade).

Color temperatures: RGB 3000K – RGB 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Contents

2	product configurator
2	diagrams / drivers



8.1" (8W) RF



8.1" (8W) RAF

Delivered Lumens*		8.1"
RA		269


*Values shown for 3000K

Xenia Recessed Blade RGBW




Ordering Information								(Required)			
XE		BL	8	8 - CCDM		RA		PWR50W-350	99933		
Product	Mounting/Frame	Type	Length	Wattage/Operation	Color Temp	Optic	+	Driver	Housing	Cables	Accessories
XE = Xenia	RF = Recessed Frameless RAF = Recessed Aluminum Frame	BL = Blade	8 = 8.1"	8 CCDM = 8W / Remote DMX Constant current 350mA driver	R3 = RGBW 3K R4 = RGBW 4K	RA = Radial (9°x>150°)		PWR50W-350	99933	E99216 E89190 E98476 E98437 E98149 E89188	(end caps) 99917 (RF) 83188 (RAF) (instl. spring) 99818 (RAF) (fixing bracket) 98949 (RF) C-F400006 (RF)

Recessed Frameless (RF) 8.1" 6W 500mA



HOUSING 99933




DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)


PWR50W-350

DMX EldoLED
POWERdrive 50W
for 1-5 fixtures

Recessed Aluminum Frame (RAF) 8.1" 6W 500mA



HOUSING 99933



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

PWR50W-350

DMX EldoLED
POWERdrive 50W
for 1-5 fixtures

Cables

E99216	E89190	E98476	E98437
59.1" power cable F 4 pin M12	196.9" power cable F 4 pin M12	59.1" power cable M 4 pin M12	39.4" extension for power cable M+F 4 pin M12
E98149	E89188		
196.9" extension for power cable M+F 4 pin M12	393.7" extension for power cable M+F 4 pin M12		

Accessories

83188	99917	99818
End caps (pair) One pair required per in-grade run for RAF	Ceiling or wall recessed installation spring for RF	Ceiling or wall recessed installation spring for RAF



98949

1.8"-2.6" Adjustable
Fixing bracket for
surface mount
applications for RF



C-F400006

Fixing bracket for RF

