



General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).

Trim: Frameless, ideal for continuous runs.

Mounting: Adjustable steel brackets available in different lengths.

Dimensions/Weight: 21.1" (1.54 lbs) – 46.5" (2.87 lbs)

Driver: Integral, 120/277V with DMX interface.

Wattages: 14.5W (21.1") – 24W (46.5")

Cable: Fixture comes with Dual 9.8" In-and-Out cables (Power, and DMX cables required, ordered separately).

Safety features: Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.

IP rating: IP66. Fixture is protected against dust and direct exposure to powerful water jets.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed. Available in Elliptical Narrow Flood – Asymmetric Wall Washer – General Distribution. Anti-glare visors available as accessory.

Color temperatures: RGB 3000K – RGB 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Contents

2	product configurator
2	diagrams / drivers




21.1" (14.5W)
46.5" (24W)


Nominal Lumens	21.1"	46.5"
Red	108	216
Green	144	288
Blue	72	144
White 3K/4K	252/275	504/550

Ordering Information										
XE	W	OB								
Product	Mounting/ Frame	Type	Length	Wattage/Operation	Color Temp	Optic	+	Cables	Fixing Brackets	Accessories
XE = Xenia	W = Wall	OB = Open Beam	21 = 21.1"	15 IDMX = 14.5W / Integral 120-277V w/DMX interface	R3 = RGBW 3K R4 = RGBW 4K	ELNFL = Elliptical Narrow Flood (41°x 102°) WW = Asymmetric Wall Washer GE = General Distribution		Feed: E83043 E83044 E83045 E83046 E83047 Dim: E89189 E89186 E98494 E98493 E98994 E98993 E89187	98949 89045 89046 89047 C-F400006 C-F400008	(Anti-glaring) 98953 (21) 98952 (47) (DMX Terminator) 89365
			47 = 46.5"	24 IDMX = 24W / Integral 120-277V w/DMX interface						

21.1" 14.5W IDMX



46.5" 24W IDMX



Cables (One Power cable, one DMX cable, and one DMX Terminator required per run)

E83043	E83044	E83045	E83046	E83047	E89189
59" line volt. power feed cable F 3 pin M12	196" line volt. power feed cable F 3 pin M12	39" line volt. power extension cable M+F 3 pin M12	196" line volt. power extension cable M+F 3 pin M12	393" line volt. power extension cable M+F 3 pin M12	196.9" DMX cable M 5 pin M12
E89186	E98494	E98493	E98994	E98993	E89187
196.9" DMX cable M 5 pin M12 + M 3 pin XLR	196.9" DMX cable M 5 pin M12 + F 3 pin XLR	196.9" DMX cable M 5 pin M12 + M 5 pin XLR	196.9" DMX cable M 5 pin M12 + M 5 pin XLR	196.9" DMX extension M+F 5 pin M12	393.7" DMX extension M+F 5 pin M12

Accessories

Steel fixing brackets		Anti-glaring accessory	
1.8-2.6"	98949	21.1"	98953
3.5"	89045	46.5"	98952
5.9"	89046		
11.8"	89047		




89365


DMX Terminator



Brackets for surface mounting



C-F400006



C-F400008