


3" ProTools+ Adjustable Square Recessed (Warm Dim)


inter•lux



Plaster Trim (RPT)



Bezel Trim (RBT)



Fixture height differs for each wattage:
6W / 9W = 3.5" (88mm)
12W = 4.3" (110mm)

Ordering Information

WG-80SPTA												
Model	Fixation	Power ¹	CRI	CCT ²	Driver ³	Cover	Lens	Beam	Trim Finish	Cover Finish	Housing ⁴	Options
WG-80SPTA	RPT RBT RWT	L M H	92	WD3018 WD2718	S010 D010 SPH D2S RS010 RD010 RD2S X	SRC	OA SOL LSL HL	15° 25° 35° 50°	W B S	MW MB SC BC	LP NC IC CP X	EM AWNRF

Luminaire

- Part of a complete family of 3" aperture high output downlights.
- 3" square aperture recessed adjustable downlight.
- Efficacy up to XX lumens per watt (delivered).
- Bridgelux LEDs.
- CRI 92+ standard.
- L70 (TM21 Projected 85°C) Warm Dim 50,000 hours.
- ETL and ETL-C for dry and damp locations.
- Luminaire installed and maintained from below the ceiling. Maximum ceiling thickness 1.2".
- Housings available (see housings page).
- 5-year warranty.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim
- RWT = Recessed Wood Trim (accessible ceiling only)

Power¹

- L = Low Power, 6.0W @ 350mA
- M = Mid Power, 9.0W @ 250mA
- H = High Power, 12.0W @ 350mA

CRI

- 92 = 92 CRI

CCT²

- WD3018 = Warm Dim 3000K - 1800K
- WD2718 = Warm Dim 2700K - 1800K

Integral Driver³

- S010 = eldoLED 0-10V 1% dimming, 120-277V (22W)
- D010 = eldoLED 0-10V 0.1% dimming, 120-277V (22W)
- SPH = Phase (2-wire) 3% dimming, 120V only (20W) (L power only)
- D2S = DALI-2 for Static White 0.1% dimming, 120-277V (22W)

Remote Driver³

- RS010 = Remote eldoLED 0-10V 1% dimming, 120-277V (22W, 50W or 100W)
- RD010 = Remote eldoLED 0-10V 0.1% dimming, 120-277V (22W, 50W or 100W)
- RD2S = Remote DALI-2 for Static White 0.1% dimming, 120-277V (22W, 50W or 100W)
- X = No driver

Cover

- SRC = Square Recessed Cone

Lens (2 accessories per fixture: SOL, LSL, HL)

- OA = Open Aperture
- SOL = Solite Lens
- LSL = Linear Spread Lens
- HL = Honeycomb Louver

Beam

- 15 = 15° Beam Angle (20° M / H)
- 25 = 25° Beam Angle
- 35 = 35° Beam Angle (40° M / H)
- 50 = 50° Beam Angle

Trim Finish

- W = White, 15% gloss, RAL 9003 (standard)
- B = Black, RAL 9017
- S = Silver, RAL 9006

Cover Finish

- MW = Matte White (standard)
- MB = Matte Black
- SC = Silver Chrome
- BC = Black Chrome

Housing (Optional)⁴

- LP = Landing Pan
- NC = New Construction Housing
- IC = Insulated Ceiling Housing
- CP = Chicago Plenum Housing
- X = No Housing

Options

- EM = Emergency (remote only)
- AWNRF = Lutron Athena Wireless Node RF (RS010, RD010, RD2S, RD2T drivers only)

1. Wattage shown does not include power supplies/drivers.

2. See photometric data sheet for delivered lumens.

3. See driver information for details.

4. See housings pages for details.