

3" ProTools+ Wallwash

Round Recessed (Tunable White)


inter•lux

Ordering Information


WG-80RPTWW												
Model	Fixation	Power ¹	CRI	CCT ²	Driver ³	Cover	Lens	Beam	Trim Finish	Cover Finish	Housing ⁴	Options
WG-80RPTWW	RPT RBT RWT	M H	92	TW2765	D2S RD2S RD2T X	RWW	WWL	WW	W B S	SCW SCB SCS MW	LP NC IC CP X	EM AWNRF



Plaster Trim (RPT)



Bezel Trim (RBT)



Fixture height differs for each wattage:
9W = 2.7" (68mm)
12W = 3.6" (92mm)

Luminaire

- Part of a complete family of 3" aperture high output downlights.
- 3" round aperture recessed wall washer.
- Efficacy up to XX lumens per watt (delivered).
- CRI 92+ standard.
- L70 (TM21 Projected 85°C) Tunable White 50,000 hours.
- ETL and ETL-C for dry and damp locations.
- Luminaire installed and maintained from below the ceiling. Maximum ceiling thickness 1.2".
- Housings available (see housings page).
- 5-year warranty.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim
- RWT = Recessed Wood Trim (accessible ceiling only)

Power¹

- M = Mid Power, 9.0W @ 250mA
- H = High Power, 12.0W @ 350mA

CRI

- 92 = 92 CRI

CCT²

- TW2765 = Tunable White 2700K - 6500K

Integral Driver³

- D2S = DALI-2 for Static White 0.1% dimming, 120-277V (22W)

Remote Driver³

- RD2S = Remote DALI-2 for Static White 0.1% dimming, 120-277V (22W, 50W or 100W)
- RD2T = Remote DALI-2 (DT8) for Tunable White 0.1% dimming, 120-277V (30W, 50W or 75W)
- X = No driver

Cover

- RWW = Round Wall Wash

Lens

- WWL = Wall Wash Spread Lens

Beam

- WW = Wall Wash

Trim Finish

- W = White, 15% gloss, RAL 9003 (standard)
- B = Black, RAL 9017
- S = Silver, RAL 9006

Cover Finish

- SCW = Silver Chrome with White Baffle, RAL 9003 (standard)
- SCB = Silver Chrome with Black Baffle, RAL 9017
- SCS = Silver Chrome with Silver Baffle, RAL 9006
- MW = Matte White

Housing (Optional)⁴

- LP = Landing Pan
- NC = New Construction Housing
- IC = Insulated Ceiling Housing
- CP = Chicago Plenum Housing
- X = No Housing

Options

- EM = Emergency (remote only)
- AAWNRF = Lutron Athena Wireless Node RF (RD2S, RD2T drivers only)

1. Wattage shown does not include power supplies/drivers.
2. See photometric data sheet for delivered lumens.
3. See driver information for details.
4. See housings pages for details.