



Contents

- 2 product configurator
- diagrams
- drivers



Ø2.8" (6.5W)

General: Buzzer Pro is part of a comprehensive family of bollards, path markers and wall fixtures designed for the most various applications, from pedestrian walkaways to public parks, commercial buildings and residential areas.

With no up-light component (Dark skies compliant), two distributions (180° and 360°) and multiple sizes available, Buzzer Pro can easily fit into every design.

Buzzer Pro's special optic design provides no shadows at the bottom of the fixture, making the ground evenly illuminated.

Fixture Body: Galvanized Iron.

Diffuser: UV Resistant Polycarbonate.

Mounting: Standard Mounting Base (Provided with fixture). Ground peg available upon request.

Dimensions/Weight: 15.75" (1.87 lbs) – 27.56" (2.83 lbs) – 35.43" (3.47 lbs).

Driver: Remote, 120-277V Dimmable 0-10V.

Wattages: 6.5W (All Sizes).

Cable: Fixture comes with 3' of power cable.

Safety features: Fixture is equipped with Electrostatic discharge protection and Surge Protection (0.5 KV).

IP rating: IP65 for protection against dust and moderate water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed, with asymmetric (180°) or round (360°) Light Emission.

Color temperatures: 2200K – 2700K – 3000K – 4000K.

CRI: 80+

BUG Rating: B0-U0-G0 (Dark Sky Compliant)

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.


Delivered Lumens*	Ø2.8" [6.5 - CC]
RE	160
AE	67

*Values shown for 3000K

Mounting Accessories

BZP				7 - CC		GE			
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required)	Mounting Accessories (optional)
BZP = Buzzer Pro	RBOBG = Round Bollard, Black Grey RBOGR = Round Bollard, Grey RBODB = Round Bollard, Dark Brown	RE = Round Emission AE = Asymmetric Emission	3x16 = Ø2.8" X 15.75"H 3x28 = Ø2.8" X 27.56"H 3x35 = Ø2.8" X 35.43"H	7 CC = 6.5W / Constant Current (350mA)	22 = 2200K 27 = 2700K 30 = 3000K 40 = 4000K	GE = General Emission		ECO30W-350 SOL050W-350 SOL0100W-350	W-F500001 (ground peg)

Ø2.8" x 15.75"H 6.5W 350mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W
for 1-2 fixtures


SOLO50W-350

0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-350

0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures

Ø2.8" x 27.56"H 6.5W 350mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W
for 1-2 fixtures


SOLO50W-350

0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-350

0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures

Ø2.8" x 35.43"H 6.5W 350mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W
for 1-2 fixtures


SOLO50W-350

0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-350

0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures

Mounting Accessories



W-F500001
(ground peg)