

Envelope IP66 Surface Mount Rectangular

inter•lux



General: With a simple, elegant, and minimalist design, Envelope is a family of round or square wall mounted step lights suitable for most projects (available for both indoor and outdoor applications). A recessed asymmetric optic that guarantees full cut-off while providing outstanding performances and a multitude of sizes and colors complete the range.

Fixture Body: Powder Coated Aluminum.

Diffuser: Silicone resin.

Mounting details: Surface mounted.

Dimensions/Weight: 4.7" x 3.5" (0.38 lbs)

Driver: Remote, Constant Voltage 24V DC, 120-277VAC Dimmable 0-10V or Non-Dim.

Wattage/Size: 1W (4.7" x 3.5")

Cable: Fixture comes with 0.98' of power cable.

IP rating: IP66 for protection against dust and water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed, Asymmetric.

Color temperatures: 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



4.7" x 3.5"(1W)


Delivered Lumens*		47 (1W)
AS		94

*Values shown for 3000K

Ordering Information							
EN66		ME	47	1 - CV		AS	
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+ Driver (Required) ¹
EN66 = Envelope IP66	SRWH = Surface Mount, Rectangular White SRWG = Surface Mount, Rectangular Grey SRBG = Surface Mount, Rectangular Black Grey SRDB = Surface Mount, Rectangular Dark Brown	ME = Mono Emission	47 = 4.7" x 3.5"	1 CV = 1W / CV = Remote Constant Voltage 24V DC	30 = 3000K 40 = 4000K	AS = Asymmetric	OT96-D010 OT96-JBX



4.7" x 3.5" (1W)



DRIVER OPTIONS (pick one)

C.V. Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location