1.5" ProTools Wall Wash Round Recessed



1.5" round aperture recessed wall wash with 1.4" half moon light aperture and internal reflector system.


Luminaire	Die-caste aluminum for precision fit and heat dissipation Mounting hardware for all ceiling types; trim and trimless EZ clip mounting for secure installation
Cover	RWW - Round Wall Wash with flush room-side cutoff and internal scoop reflector
LED	Constant Current, 92+ CRI (standard), 2-Step MacAdam Mid output (delivers up to 47 lumens per watt) 2700K, 3000K, 3500K, 4000K Warm Dim (1800 - 3000K) L70 (TM21 Projected 85° C) Static White = 33,300 hours, WD = 55,000 hours
Beam	Wall Wash
Driver	Integral and remote drivers for all Dimming and non-Dimming applications Non-Dim, 0-10V, Phase, Lutron, DALI driver options POE driver compatibility
Installation Housing	LP - Landing Pan NC - New Construction IC - Insulated Ceiling CP - Chicago Plenum X - No Housing (Optional)
Warranty	5-year Limited (see complete company warranty information)
Certifications	ETL and ETL-C for dry, damp (WL Wet Location optional), CE




Recessed Plaster Trim (RPT)




Recessed Bezel Trim (RBT)



Plaster Trim (RPT)
Cutout: Ø2.1" (54mm)



Bezel Trim (RBT)
Cutout: Ø1.8" (45mm)



Rectangular Twin Trim with Bezel Trim (RTTBT)
Cutout: 1.4" x 4.7" (60 x 120mm)

1.5" ProTools Wall Wash Round Recessed

Model	Fixation	Power[2]	CRI	CCT[3]	Driver[4,5]	Cover	Lens	Beam	Trim Finish	Housing[5]	Options
WG-40RPTWW	RBT RPT RTTBT[1]	M	92	27 30 35 40 WD	S010* D010* SPH* PEQ0* D2S* X	RWW	WWL	WW	W (std) B S F	LP NC IC CP X	WL TM EM AWNRF

*Add 'R' for remote driver, ex. 'RS010'

Model
- WG-40RPTWW = 1.5" ProTools Wall Wash Round Recessed

Fixation
- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim
- RTTBT = Rectangular Twin Trim with Bezel Trim[1]

Power[2]
- M = Mid Power, 9.1W @ 500mA

CRI
- 92 = 92 CRI

CCT[3]
- 27 = 2700K
- 30 = 3000K
- 35 = 3500K
- 40 = 4000K
- WD = Warm Dimming 1800 - 3000K

Integral Driver NC / IC / CP Housings Accessible Ceiling[4,5]
- S010 = eldoLED 0-10V 1% Dimming, 120-277V (22W)
- D010 = eldoLED 0-10V 0.1% Dimming, 120-277V (22W)
- SPH = Phase (2-wire) 3% Dimming, 120V only (20W)
- PEQ0 = Lutron Hi-Lume Premier 0.1% EcoSystem Dimming, 120-277V (20W)
- D2S = DALI-2 (DT6) for Static White 0.1% Dimming, 120-277V (22W)

Remote Driver for NC / LP / IC / CP[4,5]
- RS010 = Remote eldoLED 0-10V 1% Dimming, 120-277V (22W, 50W or 100W)
- RD010 = Remote eldoLED 0-10V 0.1% Dimming, 120-277V (22W, 50W or 100W)
- RSPH = Remote phase (2-wire) 3% Dimming, 120V only (20W)
- RPEQ0 = Remote Lutron Hi-Lume Premier 0.1% EcoSystem Dimming, 120-277V (20W)
- RD2S = Remote DALI-2 (DT6) for Static White 0.1% Dimming, 120-277V (22W, 50W or 100W)
- X = No Driver

Cover
- RWW = Round Wall Wash

Lens
- WWL = Wall Wash Spread Lens

Beam
- WW = Wall Wash

Trim Finish
- W = White, 15% gloss, RAL 9003 (standard)
- B = Black, 15% gloss, RAL 9005
- S = Silver, 15% gloss, RAL 9006
- F = Custom finish, specify RAL code

Housing (optional)[5]
- LP = Landing Pan (for remote driver)
- NC = New Construction Housing (integral driver for accessible ceilings only)
- IC = Insulated Ceiling Housing (integral driver for accessible ceilings only)
- CP = Chicago Plenum Housing (integral driver for accessible ceilings only)
- X = No Housing

Options
- WL = Wet location
- TM = Thin Metal Ceiling Clip
- EM = Emergency (remote only)
- AWNRF = Lutron Athena Wireless Node RF (RS010, RD010, RD2S drivers only)

Whitegoods reserves the right to change any information without prior notice.

Notes
1. TT Twin Trim will be provided with (2) matching fixtures, unless specified otherwise.
2. Wattage shown is for LED only, system wattage varies depending on driver selected.
3. See photometric data sheet for delivered lumens.
4. See driver information for details.
5. Refer to Housings detail page for additional information.
6. Fixture can be installed without housing.

technical information