

3" ProTools+ Downlight

Square Recessed (Tunable White)


inter•lux



Recessed Plaster Trim (RPT)



Recessed Bezel Trim (RBT)



Ordering Information

WG-80SPTDL			92			SRC						
Model	Fixation	Power ¹	CRI	CCT ²	Driver ³	Cover	Lens	Beam	Trim Finish	Cover Finish	Housing ⁴	Options
WG-80SPTDL	RPT RBT	L M H	92	TW1840 TW2765	RD2T X	SRC	OA SOL LSL HL	20° 25° 40° 50°	W B S	MW MB SC BC	LP NC IC CP X	EM AWNRF

Luminaire

- Part of a complete family of 3" aperture high output downlights.
- 3" square aperture recessed downlight.
- Bridgelux LEDs.
- CRI 92+ standard.
- L70 (TM21 Projected 85°C) Tunable White 50,000 hours.
- ETL and ETL-C for dry and damp locations.
- Luminaire installed and maintained from below the ceiling. Maximum ceiling thickness 1".
- Housings available (see housings page).
- 5-year warranty.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim

Power¹

- L = Low Power, 6.0W @ 350mA
- M = Mid Power, 9.0W @ 250mA
- H = High Power, 12.0W @ 350mA

CRI

- 92 = 92 CRI

CCT²

- TW1840 = Tunable White 1800K - 4000K
- TW2765 = Tunable White 2700K - 6500K

Remote Driver³

- RD2T = Remote DALI-2 (DT8) for Tunable White 0.1% dimming, 120-277V (30W)
- X = No driver

Cover

- SRC = Square Recessed Cone

Lens (1 accessory/lens per fixture)

- OA = Open Aperture
- SOL = Solite Lens
- LSL = Linear Spread Lens
- HL = Honeycomb Louver

Beam

- 20 = 20° Beam Angle
- 25 = 25° Beam Angle
- 40 = 40° Beam Angle
- 50 = 50° Beam Angle

Trim Finish

- W = White, RAL 9003 (standard)
- B = Black, RAL 9017
- S = Silver, RAL 9006

Cover Finish

- MW = Matte White (standard)
- MB = Matte Black
- SC = Silver Chrome
- BC = Black Chrome

Housing (Optional)⁴

- LP = Landing Pan
- NC = New Construction Housing
- IC = Insulated Ceiling Housing
- CP = Chicago Plenum Housing
- X = No Housing

Options

- EM = Emergency (remote only)
- AAWNRF = Lutron Athena Wireless Node RF (RD2T drivers only)

1. Wattage shown does not include power supplies/drivers.

2. See photometric data sheet for delivered lumens.

3. See driver information for details.

4. See housings pages for details.

CUTOUT
3.1x3.1" / 80x80mm

whitegoods

410 381 1497 inter-lux.com answers@inter-lux.com
Inter-lux reserves the right to make technical changes without notice.




Updated 10.2026 1

3" ProTools+ Downlight

Square Recessed (Tunable White)




Recessed Plaster Trim (RPT)



Low / Mid Power

High Power

Recessed Bezel Trim (RBT)



Low / Mid Power

High Power