Archiline Frameless

inter•lux

IP67

11023 lb

General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. Available in Frameless (Drive-Over) or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.



Fixed
12.6" (14.5W)
20.1" (22W)
39.4" (44W)



Darklight
12.6" (14.5W)
20.1" (22W)
39.4" (44W)

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (15 µm), Black finish
Trim: Frameless, ideal for continuous runs. Extra clear glass - Tempered
Mounting/Housing: Anodized Black (15 µm) Aluminum 6060 housing (required for in ground installations).
Drive-over: Up to 11,023 lbs.
Dimensions/Weight: 12.6" (3.31 lbs) – 20.1" (6.17 lbs) – 39.4" (10.6 lbs)

Driver: Integral 120-277V 1% (logarithmic curve) 0-10V dimming, or Non-Dim.
Wattages: 14.5W (12.6") – 22W (20.1") – 44W (39.4")
Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).
Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood – Elliptic – Asymmetric Wall Washer. Most Fixed variants are also available with Dark Light (Anti-glare) system.
Color temperatures: 2700K – 3000K – 3500K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	12.6"	20.1"	39.4"
Narrow Spot	1576	2363	4727
Spot	1416	2124	4249
Flood	1341	2011	4022
Wide Flood	1451	2177	4354
Elliptic/Grazer	1137	1705	3410
Asymm/Wall Washer	1511	2267	4534

*Values shown for 3000K

Delivered Lumens (Fixed Dark Light)*	12.6"	20.1"	39.4"
Spot	960	1570	3142
Flood	886	1450	2902
Wide Flood	1038	1698	3397
Elliptical	772	1264	2528

*Values shown for 3000K

Ordering Information

AR	RF				ID					
Product	**Mounting/ Frame**	**Type**	**Length**	**Wattage**	**Operation**	**Color Temp**	**Optic**	**+**	**Housing (Required)[2]**	**Cables[2]**
AR = Archiline	RF = Recessed Frameless	F = Fixed FDL = Fixed DarkLight	12 = 12.6"	15 = 14.5W	ID = Integral (0-10V dim)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NSP = Narrow Spot[1] SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer[1]		E98724 (12) E98725 (20) E98726 (39)	E99826 E99822 E99823 E99824 E99825
			20 = 20.1"	22 = 22W						
			39 = 39.4"	44 = 44W						

[1] Not available for FDL

[2] See page 2

Archiline Frameless

inter·lux

12.6" 14.5W ID



HOUSING

E98724
Outer Housing
12.68'' L x 2.95" W x 5.51" H



20.1" 22W ID



HOUSING

E98725
Outer Housing
20.20'' L x 2.95" W x 5.51" H



39.4" 44W ID



HOUSING

E98726
Outer Housing
39.49'' L x 2.95" W x 5.51" H



Cables 0-10V

E99826
39.4" power supply cable +0-10V dimming F 5 pin

E99822
196.9" power supply cable +0-10V dimming F 5 pin

E99823
39.4" extension cable for power +0-10V dimming M+F 5 pin

E99824
196.9" extension cable for power +0-10V dimming M+F 5 pin

E99825
393.7" extension cable for power +0-10V dimming M+F 5 pin