Archiline Frameless RGBW

inter•lux

11023 lb IP67 RGBW



12.6" (14.5W)
20.1" (24.5W)
39.4" (49W)

General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. Available in Frameless (Drive-Over) or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (15 µm), Black finish
Trim: Frameless, ideal for continuous runs. Extra clear glass - Tempered
Mounting/Housing: Anodized Black (15 µm) Aluminum 6060 housing (required for in ground installations).
Drive-over: Up to 11,023 lbs.
Dimensions/Weight: 12.6" (3.31 lbs) – 20.1" (6.17 lbs) – 39.4" (10.6 lbs)

Driver: Integral, 120-277V + DMX interface.
RGBW Color Mixing: 12.6" (3x4 LEDs) / 20.1" (5x4 LEDs) / 39.4" (10x4 LEDs)
Wattages: 14.5W (12.6") – 24.5W (20.1") – 49W (39.4")
Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).
Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer.
Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Nominal Lumens RGB/RGBW	12.6"	20.1"	39.4"
Red	177	295	590
Green	291	475	950
Blue	105	175	350
White 3K/4K	462 / 495	770 / 825	1540 / 1650

Ordering Information


AR	RF	F			IDMX					
Product	**Mounting/ Frame**	**Type**	**Length**	**Wattage**	**Operation**	**Color Temp**	**Optic**	**+**	**Housing (Required)[1]**	**Cables[1]**
AR = Archiline	RF = Recessed Frameless	F = Fixed	12 = 12.6"	15 = 14.5W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer		E98724 (12) E98725 (20) E98726 (39)	E98660 E98661 E98662 E98663 E98986
			20 = 20.1"	25 = 24.5W						
			39 = 39.4"	49 = 49W						

[1] See page 2

Archiline Frameless RGBW

inter·lux

12.6" 14.5W IDMX




HOUSING

E98724
Outer Housing
12.68'' L x 2.95" W x 5.51" H



20.1" 24.5W IDMX




HOUSING

E98725
Outer Housing
20.20'' L x 2.95" W x 5.51" H



39.4" 49W IDMX



HOUSING

E98726
Outer Housing
39.49'' L x 2.95" W x 5.51" H



Cables power+DMX

E98660
39.4" feed cable all in one power + DMX F 6 pin to bare leads

E98661
196.9" feed cable all in one power + DMX F 6 pin to bare leads

E98662
39.4" extension all in one power + DMX M+F 6 pin

E98663
196.9" extension all in one power + DMX M+F 6 pin

E98986
DMX 1200 terminator