# Guardian Wall Washer

inter•lux

IP67

**Contents**


| | |
|---|---|
| 2 | product configurator diagrams / drivers |
| 3 | photometry |






4.3" (7.2W) White Trim



4.3" (7.2W) Black Trim



4.3" (7.2W) Gray Trim

**General**: Guardian is a family of outdoor LED down lights available in different sizes, output and trim finishes. Several beam spreads, color temperatures and recessed casings suitable for brick or concrete installation make Guardian the solution for most outdoor down light needs.

**Fixture Body:** Open pore anodized and Powder Coated Die-Cast Aluminum, anodized black.
**Trim:** Open pore anodized and Powder Coated Die-Cast Aluminum. Extra-clear, Tempered glass. Available in Black, Grey and White finish. Vandal resistant: trim secured with screws.
**Mounting:** Outer casing for brick or concrete-mounted installation.
**Dimensions/Weight:** 4.3" (2.21 lbs)

**Driver:** Remote Constant Current, eldoLED 0-10V dimming (4.3").
**Wattages:** 7.2W (4.3")
**Cable:** Fixture comes with 3.28' of power cable and built-in Aquastop® (anti-wicking) system.

**IP rating:** IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.
**IK rating:** IK 10
**ETL Certification:** ETL, wet location

**Optics:** Fixed, Wall Washer.
**Color temperatures:** 2700K – 3000K – 4000K.
**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.
**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

| Delivered Lumens* | 4.3" 7.2W CC |
|---|---|
| AS | 663 |

*Values shown for 3000K

# Guardian Wall Washer

inter•lux

| Ordering Information | | | | | | | | (Required) | |
|---|---|---|---|---|---|---|---|---|---|
| GUA | | WW | 43 | 7-CC | | AS | | 99673 | |
| **Product** | **Trim** | **Type** | **Diameter** | **Wattage/Operation** | **Color Temp** | **Optic** | **+** | **Housing** | **Driver** |
| GUA = Guardian | SFWHVR = Semi Flush White Trim Vandal Resistant<br>SFBLVR = Semi-Flush Black Trim Vandal Resistant<br>SFGRVR = Semi-Flush Gray Trim Vandal Resistant | WW = Fixed Wall Washer | 43 = 4.3" | 7-CC = 7.2W / Remote Constant current (200mA) | 27 = 2700K<br>30 = 3000K<br>40 = 4000K | AS = Asymmetric Wall Washer (79°) | | 99673 | **CC:**<br>ECO30W-200<br>SOLO50W-200<br>SOLO100W-200 |

### 4.3" 7.2W CC




### RECESSED HOUSING

**99673**
Recessed casing for brick or concrete-mounted installation




### 120/277VAC DRIVER OPTIONS (pick one)

**7.2W CC Driver options (Remote Only), eldoLED 0-10V dimming:**

| **ECO30W-200 (1%)** | **SOLO50W-200 (0.1%)** | **SOLO100W-200 (0.1%)** |
|---|---|---|
| 1x fixt./driver | 1x Max./output (home-run)<br>Total 2x fixt./driver | 1x Max./output(home-run)<br>Total 4x fixt./driver |