Xenia Pro Wall Optics

inter•lux

IP66

Contents

2	product configurator
2	diagrams / drivers
3	photometry





14.4" (9W)
24.8" (17W)
36.6" (26.2W)
48.4" (35.4W)
60.2" (44W)

General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).
Trim: Frameless, ideal for continuous runs.
Mounting: Adjustable steel brackets, available in different lengths.
Dimensions/Weight: 14.4" (1.21 lbs) – 24.8" (1.76 lbs) – 36.6" (2.43 lbs) – 48.4" (3.09 lbs) – 60.2" (3.75 lbs)

Driver: Integral, 120/277VAC Non-Dim or 0-10V Dim down to 10% (Dimming N/A for 14.4").
Wattages: 9W (14.4") – 17W (24.8") – 26.2W (36.6") – 35.4W (48.4") – 44W (60.2")
Cable: IND fixtures provided with a pair of 9.8" Power in-and-out cables. ID fixtures provided with a pair of 9.8" Power in-and-out cables plus a pair of 9.8" Dimming in-and-out cables. (Power and Dimming cables required, ordered separately).
Safety features: Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.

IP rating: IP66. Fixture is protected against dust and direct exposure to powerful water jets.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Flood – Elliptic Narrow Flood – Elliptic Flood – Wall Washer. Anti-glare visors available as accessory.
Color temperatures: 2200K – 2700K – 3000K – 3500K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures.

Delivered Lumens*	14.4"	24.8"	36.6"	48.4"	60.2"
NFL	812	1623	2259	3012	3765
WW	925	1850	2574	3432	4290
ELNFL	914	1827	2542	3390	4237
ELFL	720	1439	2002	2670	3338


Xenia Pro Wall Optics

inter•lux


Ordering Information

XEP	W	OB								
Product	**Mounting/ Frame**	**Type**	**Length**	**Wattage/Operation**	**Color Temp**	**Optic**	**+**	**Cables**	**Fixing Brackets**	**Anti-glaring**
XEP = Xenia PRO	W = Wall	OB = Open Beam	14 = 14.4"	9 IND = 9W / Integral (120/277VAC Non Dim)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NFL = Narrow Flood (29°) ELNFL = Elliptic Narrow Flood (29°x 92°) ELFL = Elliptic Flood (35°x 47°) WW = Wall Washer (85°)		E83043 E83044 E83045 E83046 E83047 ID Only: E99216 E89190 E98437 E98149 E89188	98949 89045 89046 89047 C-F400006 C-F400008	98782 (14) 98783 (25) 98784 (37) 98785 (48) 99778 (60)
			25 = 24.8"	17 IND = 17W / Int. Non-dim 17 ID = 17W / Int. 0-10V dim						
			37 = 36.6"	26 IND = 26.2W / Int. Non-dim 26 ID = 26.2W / Int. 0-10V dim						
			48 = 48.4"	35 IND = 35.4W / Int. Non-dim 35 ID = 35.4W / Int. 0-10V dim						
			60 = 60.2"	44 IND = 44W / Int. Non-dim 44 ID = 44W / Int. 0-10V dim						


14.4" 9W IND




24.8" 17W IND / ID




36.6" 26.2W IND / ID



48.4" 35.4W IND / ID



60.2" 44W IND / ID



Cables

E83043	E83044	E83045	E83046	E83047
59" line volt. power feed cable F 3 pin M12	196" line volt. power feed cable F 3 pin M12	39" line volt. power extension cable M+F 3 pin M12	196" line volt. power extension cable M+F 3 pin M12	393" line volt. power extension cable M+F 3 pin M12

Dimming Cables (for ID only)

E99216	E89190	E98437	E98149	E89188
59.1" DC(+) power cable F 4 pin M12	196.9" DC(+) power cable F 4 pin M12	39" extension power cable M+F 4 pin M12	196.9" extension power cable M+F 4 pin M12	393.7" extension power cable M+F 4 pin M12

Accessories

Steel fixing brackets (Pair)

1.8-2.6"	98949
3.5"	89045
5.9"	89046
11.8"	89047



Anti-glaring accessory

14.4"	98782
24.8"	98783
36.6"	98784
48.4"	98785
60.2"	99778



C-F400006 (Pair)



C-F400008 (Pair)

